



Interciencia

ISSN: 0378-1844

interciencia@ivic.ve

Asociación Interciencia

Venezuela

Rendón Hernández, Fabián Jesús; Gutiérrez-Díaz, José Luis; Silva Martínez, Susana; Hernández, J. A.; Álvarez-Gallegos, Alberto

Castor biodiesel-diesel blend to power a diesel engine: evaluation of the bus efficiency and emissions under driving conditions

Interciencia, vol. 40, núm. 1, enero, 2015, pp. 32-37

Asociación Interciencia

Caracas, Venezuela

Available in: <http://www.redalyc.org/articulo.oa?id=33933115005>

- How to cite
- Complete issue
- More information about this article
- Journal's homepage in redalyc.org

redalyc.org

Scientific Information System

Network of Scientific Journals from Latin America, the Caribbean, Spain and Portugal

Non-profit academic project, developed under the open access initiative

---

**CASTOR BIODIESEL-DIESEL BLEND TO POWER A DIESEL ENGINE:  
EVALUATION OF THE BUS EFFICIENCY AND EMISSIONS UNDER  
DRIVING CONDITIONS**

---

Fabián Jesús Rendón Hernández, José Luis Gutiérrez Díaz, Susana Silva Martínez,  
J. A. Hernández and Alberto Álvarez Gallegos

**SUMMARY**

*Biodiesel produced from castor oil has attractive properties as this fuel can be produced from renewable energy sources without compromising food supply. A B20 castor biodiesel-diesel blend was used on a diesel engine without any other modification. A field study was conducted on a diesel school bus in the state of Morelos, Mexico, to evaluate fuel efficiency and fuel emissions from diesel and from the B20 castor biodiesel-diesel blend under bus driving conditions on the highway and in the urban area. Refined castor oil was*

*used to produce biodiesel at pilot scale (300 liters) in compliance with the B100 ASTM D6751 standard. The results show the benefits of using castor biodiesel since, when compared to diesel fuel, similar fuel efficiencies and reductions in exhaust emissions were accomplished with the B20 castor biodiesel-diesel blend. This blend represents an environmental-friendly alternative to reduce diesel consumption without threatening the food supply, because castor biodiesel is produced from wild plant oil.*

**Introduction**

Air pollution, climate change and reduced availability of fossil fuels have shifted the manner in which this traditional energy source is exploited and used. Renewable

energy sources lessen the impact of environmental contamination. A feasible environmental alternative are the bio-fuels, known as 'green energy' sources. Green energy is essential to achieve the ultimate goal of sustainability since it

may minimize environmental affectation and economic and social impact (Salvi and Panwar, 2012). Green energy is, consequently, a major factor in future sustainable development and world stability (Midilli *et al.*, 2007). Biodiesel

is biodegradable and renewable, less toxic for the environment compared to conventional diesel and it does not contribute to global warming, due to its closed carbon cycle (Van Gerpen, 2005). Biodiesel can be produced from various

---

**KEYWORDS / Biodiesel Standard / Castor Biodiesel-Diesel Blend / Diesel School Bus / Emissions / Fuel efficiency /**

---

Receipt: 09/26/2013. Modified: 12/02/2014. Accepted: 12/09/2014.

**Fabián Jesús Rendón-Hernández.** M.I.C.A. and doctoral candidate in Engineering and Applied Sciences, Universidad Autónoma del Estado de Morelos (UAEM).

**José Luis Gutiérrez-Díaz.** M.I.C.A. and doctoral candidate in Engineering and Applied Sciences, UAEM, Mexico.

**Susana Silva Martínez.** Chemical Engineer, Instituto Tecnológico de Zacatepec, Mexico. Ph.D. in Electrochemistry, University of Southampton, RU. Professor, UAEM, Mexico.

**J. A. Hernández.** Chemical Engineer, Universidad Veracruzana, Mexico. Ph.D. in Process Engineering, École

Nationale Supérieure des Industries Agro-Alimentaires (ENSIA), France. Professor, UAEM, Mexico.

**Alberto Álvarez-Gallegos.** Chemical Engineer, Universidad Michoacana, Mexico. Ph.D. in Electrochemistry, University of Southampton, RU. Professor, UAEM, Mexico.

Address: Centro de Investigación en Ingeniería y Ciencias Aplicadas, UAEM. Av. Universidad 1001, Col. Chamilpa, Cuernavaca, Mor. Mexico. e-mail: aalvarez@uaem.mx

## MEZCLA DE BIODIESEL DE RICINO-DIESEL PARA PONER EN FUNCIONAMIENTO UN MOTOR DIESEL: EVALUACIÓN DE LA EFICIENCIA Y EMISIONES DE UN AUTOBÚS CONDUCIDO EN CONDICIONES REALES

Fabián Jesús Rendón Hernández, José Luis Gutiérrez Díaz, Susana Silva Martínez, J. A. Hernández y Alberto Álvarez Gallegos

### RESUMEN

*El biodiesel producido a partir de aceite de ricino tiene propiedades atractivas debido a que este combustible puede ser producido de fuentes de energía renovable sin comprometer el suministro de alimentos. La mezcla B20 de biodiesel de ricino-diesel fue utilizada sin otra modificación para alimentar un motor diesel de un autobús escolar. Las eficiencias y emisiones de los combustibles diesel y mezcla B20 fueron evaluadas bajo condiciones reales de conducción del autobús, tanto en la autopista como en la zona urbana en el estado de Morelos, México. El biodiesel fue producido conforme a la norma*

*B100 ASTM D 6751 a escala piloto (300 litros) a partir de aceite de ricino refinado. Este estudio demostró los beneficios de usar biodiesel de ricino debido a que el combustible B20 mostró que la eficiencia y las reducciones en las emisiones en el escape fueron similares a las obtenidas con el combustible diesel. La mezcla B20 de biodiesel de ricino-diesel representa una alternativa ambiental para reducir el consumo de diesel sin poner en peligro el suministro de alimentos, ya que el biodiesel es producido a partir del aceite de ricino proveniente de plantas silvestres.*

## MISTURA DE BIODIESEL DE RICINO-DIESEL PARA POR EM FUNCIONAMENTO UM MOTOR DIESEL: AVALUAÇÃO DA EFICIÊNCIA E EMISSÕES DE UM ÔNIBUS CONDUZIDO EM CONDIÇÕES REAIS

Fabián Jesús Rendón Hernández, José Luis Gutiérrez Díaz, Susana Silva Martínez, J. A. Hernández e Alberto Álvarez Gallegos

### RESUMO

*O biodiesel produzido a partir de óleo de ricino tem propriedades atrativas devido a que este combustível pode ser produzido de fontes de energia renovável sem comprometer o subministrio de alimentos. A mistura B20 de biodiesel de ricino-diesel foi utilizada sem outra modificação para alimentar um motor diesel de um ônibus escolar. As eficiências e emissões dos combustíveis diesel e mistura B20 foram avaliadas sob condições reais de condução do ônibus, tanto em autopista como na zona urbana no estado de Morelos, México. O biodiesel foi produzido con-*

*forme à norma B100 ASTM D 6751 a escala piloto (300 litros) a partir de óleo de ricino refinado. Este estudo demonstrou os benefícios de usar biodiesel de ricino devido a que o combustível B20 mostrou que a eficiência e as reduções nas emissões no escape foram similares às obtidas com o combustível diesel. A mistura B20 de biodiesel de ricino-diesel representa uma alternativa ambiental para reduzir o consumo de diesel sem por em perigo o subministrio de alimentos, já que o biodiesel é produzido a partir do óleo de ricino proveniente de plantas silvestres.*

edible biolipids (rapeseed, soybean, sunflower and palm virgin oils, from waste vegetable oil, as well as from animal fats) and non-edible ones (jatropha, neem oil, castor oil, tall oil). Biodiesel is most commonly produced by the base catalyst transesterification of vegetable oils, since this process is carried out at relatively low temperature and atmospheric pressure, resulting in lower capital and operating costs for the biodiesel plant (Demirbas *et al.*, 2009). The composition of fatty acid methyl esters produced by transesterification of vegetable oil determines the physical and chemical properties of the biodiesel, which in turn influence the efficiency of a diesel engine and its emissions (Klopfenstein, 1985; Peterson and Reece, 1996; Munoz *et al.*, 2004; Chhina *et al.*, 2005;

Szybist *et al.*, 2007; Tat *et al.*, 2007; Lapuerta *et al.*, 2008; Ozcanli *et al.*, 2011; Panwar *et al.*, 2010; Siva *et al.*, 2011; Chauhan *et al.*, 2012; Pattamaproma *et al.*, 2012; Salvi and Panwar, 2012).

Biodiesel represents a renewable and environmentally friendly alternative for the transport sector. For use as diesel fuels, vegetable and animal fats and oils undergo a transesterification process to improve the fuel combustion characteristics of biolipids by reducing their viscosity. Salvi and Panwar (2012) reviewed biodiesel resources and the production technologies for large scale and sustainable production of biodiesel. These authors concluded, from many case studies, that engine efficiency with B20 biodiesel blends and mineral diesel were comparable (the most common

blends of biodiesel contain 20% biodiesel and 80% conventional diesel). Also, based on the increasing interest in the use of biodiesel as an alternative to conventional diesel, the U.S. Environmental Protection Agency (EPA, 2002) conducted a comprehensive analysis of the emission impacts of biodiesel using available data from heavy-duty diesel-powered highway engines. It was reported that biodiesel impact on emissions varied depending on the type of biodiesel (biolipids source) and on the type of conventional diesel used to be blended with the biodiesel. The report also highlighted that the use of biodiesel increases nitrogen oxides (NOx) emissions; although the increase is small in comparison to the reductions in other regulated pollutants. Therefore, additional research

was suggested so as to find ways to mitigate the NOx increase (EPA, 2002). Pillay *et al.* (2013) employed a high-performance instrument to study the levels of CO<sub>2</sub>, NOx, and toxic gas (such as CO, NO, SO<sub>2</sub>) emissions in blended mixtures of neem biodiesel with commercial diesel, and compared the overall combustion efficiency with that of diesel. These authors found that the 95/5% (diesel/neem biodiesel) blend compared reasonably well with pure petroleum diesel, in terms of combustion efficiency, while the main drawback was the elevated production of NO and NOx as in the diesel.

The aim of the present study was to produce B100 castor biodiesel in a pilot plant in compliance with the ASTM D6751 standard and to study the emissions and

engine efficiency of a diesel school bus fuelled with diesel and B20 castor biodiesel-diesel blend, travelling on the highway and the urban area.

## Materials and Methods

### Chemicals

Edible refined castor oil (purchased from a Mexican store, Aceites y Maquilas S.A.) and ultra-low sulphur diesel (purchased from service stations) were used as received, without further purification. The industrial grade chemical reagents involved in the transesterification process were sulphuric acid, sodium hydroxide, and 99% methanol. Tap water was used to prepare all solutions.

### Pilot plant biodiesel production

The transesterification reaction took place in a 300 liters commercial complete-biodiesel-processor Fuel Meister II<sup>TM</sup> (Home BioDiesel). Biodiesel production was carried out following the step-by-step procedure described in the equipment manual. Briefly, the main steps were: methoxide formation, transesterification reaction, glycerin separation, biodiesel water washing and drying, biodiesel filtration, biodiesel and glycerin storage, and alcohol recuperation. To produce the methoxide, a methanol:oil molar ratio of 2.9:1 was used and 0.233 mol·mol<sup>-1</sup> at 1%wt of NaOH catalyst was mixed with methanol. The amount of catalyst (Singh *et al.*, 2006) was obtained according to the molecular weight of castor oil (932.0 g·mol<sup>-1</sup>; Loaiza, 2003). Mixing of methanol (9.72 liters) with the catalyst took place inside a reactor under reflux for ~30min or until the catalyst was completely diluted in the alcohol, forming methoxide. This was followed by addition of hot vegetable oil (80 liters) to be mixed with the methoxide under reflux for ~3h. The refined castor oil was previously heated to 50-55°C by means of electrical resistances. After the reaction

time, the methyl esters were separated from the glycerin by settling for 24h, followed by water washing and drying. The water (200ml of tap water were used per liter of biodiesel) was introduced from the top of the reactor by mixing at the time of entering in contact with the biodiesel. At this stage the biodiesel becomes cloudy, and is then allowed to rest for 24h in order to separate biodiesel impurities (glycerol) that are then drained. This washing procedure was repeated three times and the biodiesel became less cloudy after each wash. The drying procedure was carried out by heating the biodiesel to 100°C for 15min after the last wash, so as to evaporate the excess water and recover the golden color of the oil. Higher temperatures were avoided to prevent the biodiesel from being burnt. Once the biodiesel was cold, it was filtered using a funnel and filter for biodiesel and placed in a storage container. At this stage, the B20 castor biodiesel-diesel blend was prepared by mixing 20 parts of castor biodiesel with 80 parts of diesel. Finally, the alcohol was recovered through distillation and the glycerin was used as an additive to manufacture soap by saponification. The biodiesel produced from refined castor oil was analysed for kinematic viscosity, flash point, cloud point, sulphur and carbon residue (Conradson), water and sediment content, free glycerine and sulphate ash. Standard methods and standard procedures were used in the biodiesel characterization (ASTM D 6751).

### Bus wear and driving conditions

The diesel school bus (urban bus Mercedes Benz, year 2000, capacity 34 seats, motor 4 CIL 190 HP transmission of 5 Vel. with Dual) used for the emissions and efficiency test showed an initial wear in its mechanical components, since it had been used for about 100000km with diesel prior to being used in this study. The

bus was always driven by the same driver and the driving speeds were similar during all the tests of the diesel and B20 castor biodiesel-diesel blend. The B20 castor biodiesel-diesel blend was prepared and immediately loaded in the fuel tank as soon as the B100 castor biodiesel was produced. Average speeds were 80km·h<sup>-1</sup> on the highway and 40km·h<sup>-1</sup> in the urban area. Bus exhaust emissions were measured using the Unigas 3000 MKIII equipment (Cole-Palmer). At the start of each bus test the fuel tank was totally drained out; then, a known amount of fuel was fed into it. At the end of the bus test, the tank was totally drained again and the remaining fuel was measured with a graduated 20 liter container. The difference in volume was the fuel consumed during the bus test.

## Results and Discussion

### Biodiesel production at pilot plant scale

The castor biodiesel production and its characterization in compliance with the B100 ASTM D6751 standard requires special facilities and such characterization is expensive to be carried out routinely. The B100 castor biodiesel obtained from refined castor oil was almost fully characterized, as shown in Table I. As can be seen, all the main parameters were within the limits established by B100 ASTM D6751, except for the kinematic viscosity, which is higher than the standard value. However, this parameter falls within the standard limits, as a B20 biodiesel-diesel blend is used in the diesel engine of the school bus.

These results demonstrate that high quality biodiesel can be produced with the procedure described in the pilot plant manual. The kinematic viscosity (Table II) of B100 castor biodiesel is very high compared to B100 ASTM D6751 standard value. This high value is attributed to hydrogen bonding of hydroxyl groups in ricinoleic acid

(Ogunniyi, 2006). Also, a high correlation was found (Kim *et al.*, 2010) between oil viscosity and fatty acid composition, where the flow behavior of castor oil was positively governed by its major components (oleic acid 18:1, and linoleic acid 18:2 fatty acids). Nevertheless, the B20 castor biodiesel-diesel blend, used as biofuel in the school bus in the present study was within the limits established by the biodiesel standard, as shown in Table II. The castor biodiesel displayed a clear, bright and golden color without impurities during the visual inspection. The HPLC analyses revealed that castor biodiesel was mainly composed of a mixture of five fatty acid methyl esters.

The fatty acid methyl esters found in the produced biodiesel (Table III) are palmitic (hexadecanoic) acid, linoleic acid, oleic acid, and stearic (octadecanoic) acid, which correspond with biodiesel feedstock such as corn and rapeseed oils (Knothe, 2008), whereas the methyl ricinoleate in the castor biodiesel corresponds to the ricinoleic acid in the castor oil (Knothe, 2008). These fatty acid methyl esters found in the biodiesel may give an estimation of the cetane number in the biofuel produced in the pilot plant. The cetane number is related to the ignition quality of a fuel in a diesel engine and its determination biodiesel is expensive (Gopinath *et al.*, 2009; Knothe *et al.*, 2003). It has been reported (Gopinath *et al.*, 2009) that the cetane number of biofuels is considerably influenced by their fatty acid methyl ester composition, and a model proposed to predict this ignition quality parameter of biodiesels based on such composition. It is desirable that fuels exhibit high cetane number (Van Gerpen *et al.*, 2006). The cetane number of diesel is 40, whereas 47 is the cetane number for biodiesel to comply with ASTM D 6751. Thus, according to Tables III and IV, the biofuel produced in the pilot plant may exhibit the minimum required value.

TABLE I  
ANALYSIS OF B100 CASTOR BIODIESEL PRODUCED FROM REFINED  
CASTOR OIL AT PILOT PLANT SCALE FOR QUALITY CONTROL

Parameter / Units	B100 Castor oil	Biodiesel B100 ASTM specification (Pillay <i>et al.</i> , 2013)
Visual inspection	Clear and bright, without impurities	
Kinematic viscosity (mm <sup>2</sup> s <sup>-1</sup> , at 40°C)	26.2	1.9-6.0
Flash point (°C)	202	>130
Cloud point (°C)	-18	It has to be reported
Sulfur (wt.%)	0.02	<0.05
Carbon residue (wt.%)	0.04	<0.05
Water and sediments (wt.%)	Traces	<0.02
Free glycerine (wt.%)	Traces	<0.02
Sulfate ash (wt.%)	0.03	<0.02

TABLE II  
PARAMETERS ANALYZED ON B100 CASTOR BIODIESEL PRODUCED FROM REFINED  
CASTOR OIL IN THE PILOT PLANT AND B20 CASTOR BIODIESEL-DIESEL BLEND

Parameter	Diesel ASTM D975-05 (Van Gerpen <i>et al.</i> , 2006)	Castor biodiesel B100	B20	Biodiesel ASTM D6751 (Van Gerpen <i>et al.</i> , 2006)
Visual inspection		Clear and bright without impurities		
Kinematic viscosity (mm <sup>2</sup> s <sup>-1</sup> , 40°C)	1.3-5.5	26.2	5.69	1.9-6.0
Free glycerin		Traces	Traces	<0.02

TABLE III  
REPORTED VALUES OF THE CETANE NUMBER FROM THE MAIN FATTY ACID  
METHYL ESTERS PRESENT IN THE BIODIESEL PRODUCED IN THE PILOT PLANT

Fatty acids / Methyl-ester	Molecular formula	Molecular weight	Cetane number of pure fatty acid methyl esters	
			Experimental value (Knothe, 2008)	Average theoretical value (Gopinath <i>et al.</i> , 2009)
Methyl palmitate	C <sub>17</sub> H <sub>34</sub> O <sub>2</sub>	270.5	85.9	76.6
Methyl linolate	C <sub>19</sub> H <sub>34</sub> O <sub>2</sub>	294.5	38.2	39.2
Methyl oleate	C <sub>19</sub> H <sub>36</sub> O <sub>2</sub>	296.5	56.55	56.9
Methyl stearate	C <sub>19</sub> H <sub>38</sub> O <sub>2</sub>	298.5	101	85.9
Methyl ricinoleate	C <sub>19</sub> H <sub>36</sub> O <sub>3</sub>	312.5	37.38	42

Table III shows the molecular formulas for the methyl esters present in the castor biodiesel produced in the pilot plant, as well as the theoretical (Gopinath *et al.*, 2009) and experimental (Knothe, 2008) cetane number of pure fatty acid methyl esters found in the biodiesel produced. Table IV also shows experimental values for cetane number of diesel and B100 biodiesels reported in the literature (Pillay *et al.*, 2013; Gopinath *et al.*, 2009; Bello and Makanju, 2011). It is expected that the castor biofuel produced here have the minimum standard value since the procedure used in the pilot plant produces a high quality biodiesel.

TABLE IV  
EXPERIMENTAL VALUES REPORTED  
FOR CETANE NUMBER OF DIESEL AND B100  
CASTOR BIODIESEL-DIESEL BLEND PRODUCED  
IN THE PILOT PLANT

Fuel	Average value*	Standard value**
Diesel	47.4	40 (ASTM D975)
Castor biodiesel	53.0	47 (ASTM D6751)

\* Bello and Makanju (2011).

\*\* Gopinath *et al.* (2009).

#### Bus efficiency and gas emissions

Several studies have reported the benefits of using biodiesel and biodiesel-diesel blends as an alternative to

diesel since biodiesel has a positive impact in the environment with fewer atmospheric emissions (Kalligeros *et al.*, 2003; Demirbas, 2007; Hess *et al.*, 2007; Lechon *et al.*, 2009; Gokalp *et al.*, 2011). The

main emissions from biodiesel are CO, CO<sub>2</sub>, NO<sub>x</sub>, SO<sub>2</sub> and smoke (Basha *et al.*, 2009). B20 biodiesel blends are more commonly used in diesel engines. It is evident that biodiesel impacts on emissions vary depending on the type of biodiesel (soybean, palm, castor, rapeseed, animal fats, etc) and on the type of conventional diesel to which the biodiesel is added (EPA, 2002). In this study, the B20 castor biodiesel-diesel blend was used to evaluate bus engine efficiency in fuel consumption and exhaust emissions. Table V shows the travelling bus conditions, such like distance travelled, bus load (with or without passengers), travel on the highway or in the urban area, average speed and bus engine efficiency on fuel consumption. The consumption of fuel on the highway and in the urban area with no passengers on the bus was similar for both fuels. Conversely, on the highway, with a loaded bus to its maximal capacity, with 34 passengers, the bus engine efficiency using diesel was 13% higher than with B20 castor biodiesel. Diesel fuel showed higher fuel efficiency than B20 castor biodiesel-diesel blend regardless of the test driving conditions. This was attributed to the higher calorific value that diesel fuel has compared to biodiesel (Basheer *et al.*, 2012).

Table VI reports emissions of O<sub>2</sub>, CO, NO, NO<sub>x</sub> and SO<sub>2</sub> for B20 castor biodiesel-diesel blend and diesel for a bus travelling on the highway and in the urban area. O<sub>2</sub> emissions were slightly higher with respect to diesel for B20 castor biodiesel-diesel blend. The higher O<sub>2</sub> content in the biofuel is part of the oxygenated nature of biodiesels, which contributes to more complete combustion and lower emissions (Murillo *et al.*, 2007), as shown in the results reported on Table VI. CO emissions were similar for both fuels on the urban area and on the highway. Lower bus emissions were detected for B20 castor biodiesel-diesel blend in the



TABLE V  
DIESEL SCHOOL BUS DRIVEN USING DIESEL AND CASTOR BIODIESEL-DIESEL  
BLEND PRODUCED IN A PILOT PLANT (AVERAGE SPEED: 80 km·h<sup>-1</sup> ON  
THE HIGHWAY AND 40 km·h<sup>-1</sup> IN THE URBAN AREA)

Fuel	Distance travelled on highway (km)	Bus condition	Bus engine efficiency (km·l <sup>-1</sup> )	Distance travelled in urban area (km)	Bus condition	Bus engine efficiency (km·l <sup>-1</sup> )
Diesel	80	No passengers	4.7	11	No passengers	3.7
	94	34 passengers	3.8	82	34 passengers	3.6
B20 Castor biodiesel diesel blend	81	No passengers	4.7	13	No passengers	3.6
	81	34 passengers	3.3	13	34 passengers	3.2

TABLE VI  
EMISSIONS FROM A SCHOOL BUS DRIVEN  
IN THE URBAN AREA AND ON THE HIGHWAY

Gas	Urban area		Highway	
	Diesel	B20 castor biodiesel	Diesel	B20 castor biodiesel
O <sub>2</sub> (%)	18.5	19.1	18.6	19.1
CO <sub>2</sub> (%)	1.8	1.4	1.8	1.4
CO (ppm)	254	231	179	161
NO (ppm)	155	154	133	131
NO <sub>x</sub> (ppm)	160	163	137	135

dl: detection limit.

urban area except for NO and NO<sub>x</sub> which were similar to diesel fuel. In all cases, SO<sub>2</sub> was always below the detection limit. The use of B20 castor biodiesel-diesel blend yielded an important reduction of greenhouse gases such as CO<sub>2</sub> and CO in the urban area. However, regarding the amount of CO<sub>2</sub> gas emitted to the atmosphere, it should be considered that it was already available in the atmosphere to be used by the castor plant in its vital process of photosynthesis to produce its oil seeds. Therefore, the released CO<sub>2</sub> during the combustion process of B20 castor biodiesel-diesel blend has no additional negative effects to the environment, as CO<sub>2</sub> is recycled through the photosynthesis process by plants and trees; even by the next castor crops.

A review of the influence of fuel properties and fuel composition on NO<sub>x</sub> emissions from biodiesel powered diesel engines was written by Varatharajan and Cheralathan (2012). In that review, it was highlighted that most of the

studies have shown that NO<sub>x</sub> emissions from biodiesel increased, as compared with diesel. Also, the authors concluded that the exact cause of this increase is still unclear and, according to the revised studies, the fuel properties have been shown to effect the NO<sub>x</sub> emissions. In our study, NO and NO<sub>x</sub> emissions were similar for both diesel and B20 castor biodiesel-diesel blend. It was reported that biodiesel with high cetane numbers had NO<sub>x</sub> emissions comparable to those of diesel (Varatharajan and Cheralathan, 2012). Also, the value of the iodine number influences the NO<sub>x</sub> emissions since iodine number is a measure of unsaturation degree of the fatty acid; thus, a high iodine number indicates a high degree of unsaturation (McCormick *et al.*, 2001). The latter authors reported a relationship between NO<sub>x</sub> emissions and iodine value of biodiesel, and found that NO<sub>x</sub> increases with the iodine value of the biofuel. Tat *et al.* (2007) reported that NO<sub>x</sub> emissions were significantly reduced

from an engine fueled with unsaturated biodiesel from high-oleic soybeans.

## Conclusions

The pilot scale process for the production of B20 castor biodiesel-diesel blend complied with the ASTM D6751 standard. B20 castor biodiesel-diesel blend showed similar efficiency to that of diesel in fuel consumption. CO emissions were similar for both fuels on the urban area and on the highway. B20 castor biodiesel-diesel blend produced less exhaust emissions in the urban area as compared to diesel except for NO and NO<sub>x</sub>, which were similar. The results obtained in this study demonstrate that B20 castor biodiesel-diesel blend shows good performance and can gradually be introduced as biofuel for the diesel engines of the school buses and shuttle buses that travel in the campus of the Autonomous University of Morelos State without putting at risk the diesel engines and food supply, since this biodiesel is B100 ASTM compliant and was made out of an oil that is unsuitable for human consumption. Additionally, the methodology developed in this work can be spread out in different regions of the Morelos State in order to contribute to a cleaner air and a better environment. However, the availability of castor oil represents a very important challenge since this oil is not produced in Mexico; thus, a feasibility study for castor seed crops and castor oil extraction

in a large scale is needed to introduce the biodiesel as environmental biofuels in the State in the near future.

## ACKNOWLEDGMENTS

The authors thank Fernando de Jesus Bilbao Marcos (ex-Rector UAEM) by the donation of the bus through CHICAP-UAEM; Melchor Araujo Macedo, Alejandro Vera Jimenez, Carlos Medina and Carlos Ortega for their help in this study; CONACYT for the postgraduate study grants to J.F.R.H. and J.L.G.D. This work was financially supported by PIFI and PROMEP Programs of the Secretaría de Educación Pública, Mexico.

## REFERENCES

- Basha SA, Gopal KR, Jebaraj S (2009) A review on biodiesel production, combustion, emissions and performance. *Renew. Sust. Energy Rev.* 13: 1628-1634A.
- Basheer H, Diya'uddeen, Aziz ARA, Daud WMAW, Chakrabarti MH (2012) Performance evaluation of biodiesel from used domestic waste oils: A review. *Proc. Saf. Environ.* 90: 164-179.
- Bello EI, Mekanju A (2011) Production, characterization and evaluation of castor oil biodiesel as alternative fuel for diesel engines. *J. Emerg. Trends Eng. Appl. Sci.* 2: 525-530.
- Chauhan BS, Kumar N, Cho HM (2012) A study on the performance and emission of a diesel engine fueled with Jatropa biodiesel oil and its blends. *Energy* 37: 616-622.
- Chhina R, Verma SR, Sharda A (2005) Exhaust emission characteristics of an unmodified diesel engine operated on bio-diesel fuels. *J. Agric. Eng.* 42: 38-43.
- Demirbas A (2007) Importance of biodiesel as transportation fuel. *Energy Policy* 35: 4661-4670.
- Demirbas MF, Balat M, Balat H (2009) Potential contribution of biomass to the sustainable energy development. *Energy Convers. Manag.* 50: 1746-1760.
- EPA (2002) *A comprehensive Analysis of Biodiesel Impacts on Exhaust Emissions*. Draft Technical Report. United States Environmental Protection Agency. Air and Radiation EPA 420-P-02-001.

- Gokalp B, Buyukkaya E, Soyhan HS (2011) Performance and emissions of a diesel tractor engine fueled with marine diesel and soybean methyl ester. *Biomass Bioenergy* 35: 3575-3583.
- Gopinath A, Puhan S, Nagarajan G (2009) Relating the cetane number of biodiesel fuels to their fatty acid composition: A critical study. *J. Automob. Eng.* 223: 565-583.
- Hess MA, Haas MJ, Foglia TA (2007) Attempts to reduce NOx exhaust emissions by using reformulated biodiesel. *Fuel Proc. Technol.* 88: 693-699.
- Kalligeros S, Zannikos F, Stournas S, Lois E, Anastopoulos G, Teas Ch, Sakellaropoulos F (2003) An investigation of using biodiesel/marine diesel blends on the performance of a stationary diesel engine. *Biomass Bioenergy* 24: 141-149.
- Kim J, Kim DN, Lee SH, Yoo S-H, Lee S (2010) Correlation of fatty acid composition of vegetable oils with rheological behaviour and oil uptake. *Food Chem.* 118: 398-402.
- Klopfenstein W (1985) Effect of molecular weights of fatty acid esters on cetane numbers as diesel fuels. *J. Am. Oil Chem. Soc.* 62: 1029-1031.
- Knothe G (2008) "Designer" biodiesel: Optimizing fatty ester composition to improve fuel properties. *Energy Fuels* 22: 1358-1364.
- Knothe G, Matheaus AC, Ryan TW (2003) III. Cetane numbers of branched and straight-chain fatty esters determined in an ignition quality tester. *Fuel* 82: 971-975.
- Lapuerta M, Armas O, Rodriguez-Fernandez J (2008) Effect of biodiesel fuel on diesel engine emission. *Prog. Energy Combust. Sci.* 34: 198-223.
- Lechon Y, Cabal H, de la Rua C, Caldes N, Santamaria M, Saez R (2009) Energy and greenhouse gas emission savings of biofuels in Spain's transport fuel. The adoption of the EU policy on biofuels. *Biomass Bioenergy* 33: 920-932.
- Loaiza RFE (2003) *Cinética de la Reacción de Transesterificación del Aceite de Higuera en la Obtención de Biodiesel*. Tesis. Universidad Nacional de Colombia. 13 pp.
- McCormick R, Graboski M, Alleman T, Herring A, Tyson S (2001) Impact of biodiesel source material and chemical structure on emissions of criteria pollutants from a heavy-duty engine. *Environ. Sci. Technol.* 35: 1742-1747.
- Midilli A, Dincer I, Rosen MA (2007) The role and future benefits of green energy. *Int. J. Green Energy* 4: 65-87.
- Munoz M, Moreno F, Morea J (2004) Emission of an automobile diesel engine fueled with sunflower methyl ester. *Trans ASAE*. 47: 5-11.
- Murillo S, Míguez JL, Porteiro J, Granada E, Morán JC (2007) Performance and exhaust emissions in the use of biodiesels in outboard diesel engines. *Fuel* 86: 1765-1771.
- Ogunniyi DS (2006) Castor oil: A vital industrial raw material. *Bioresource Technol.* 97: 1086-1091.
- Ozcanli M, Keskin A, Aydin K (2011) Biodiesel production from terebinth (*Pistacia terebinthus*) oil and its usage in diesel engine. *Int. J. Green Energy* 8: 518-528.
- Panwar NL, Shrirame HY, Rathore N, Jindal S, Kurchania AK (2010) Performance evaluation of a diesel engine fueled with methyl ester of castor seed oil. *Appl. Therm. Eng.* 30: 245-249.
- Pattamaproma C, Pakdeeb W, Ngamjaroen S (2012) Storage degradation of palm derived biodiesels: its effects on chemical properties and engine performance. *Renew. Energy* 37: 412-418.
- Peterson C, Reece D (1996) Emission characteristics of ethyl and methyl ester of rapeseed oils compared with low sulfur diesel control fuel in a chassis dynamometer test of a pickup truck. *Trans ASAE* 39: 805-816.
- Pillay A, Molki A, Elkadi M, Manuel J, Bojanampati S, Khan M, Stephen S (2013) Real-time study of noxious gas emissions and combustion efficiency of blended mixtures of neem biodiesel and diesel. *Sustainability* 5: 2098-2107.
- Salvi BL, Panwar NL (2012) Biodiesel resources and production technologies -A review. *Renew. Sust. Energy Rev.* 16: 3680-3689.
- Singh A, He B, Thompson J, Van Gerpen J (2006) Process optimization of biodiesel production using alkaline catalysts. *Appl. Eng. Agric.* 22: 597-600.
- Siva RV, Ranjan KR, Sharma VK, Tyagi SK (2011) Experimental investigation of a diesel engine fuelled with *Jatropha curcas* L. seed oil. *Int. J. Sustain. Energy* 31 (Suppl 1): S4-10.
- Szybist JP, Song J, Alam M, Boehman AL (2007) Biodiesel combustion, emission and emission control. *Fuel Proc. Technol.* 88: 679-691.
- Tat M, Paul S, Gerpen J (2007) Exhaust emissions from an engine fueled with biodiesel from high-oleic soybeans. *J. Am. Oil Chem Soc.* 84: 865-869.
- Van Gerpen J, Pruszkowski R, Clements D, Shanks B, Knothe G (2006) *Building a Successful Biodiesel Business*. 2<sup>nd</sup> ed. Biodiesel Basics. Dubuque, IO, USA. pp. 14, 31.
- Van Gerpen J. Biodiesel processing and production (2005) *Fuel Proc. Technol.* 86: 1097-1107.
- Varatharajan K, Cheralathan M (2012) Influence of fuel properties and composition on NOx emissions from biodiesel powered diesel engines: A review. *Renew. Sust. Energy Rev.* 16: 3702-3710.