



Revista Facultad Nacional de Agronomía Medellín

ISSN: 0304-2847

ISSN: 2248-7026

Facultad de Ciencias Agrarias - Universidad Nacional de Colombia

Jaramillo-Garcés, Yamilé; Sacchet-Pérez, Miguel; Manjarres-Pinzon, Gustavo;
Manjarres-Pinzon, Katherine; Correa-Londoño, Guillermo; Rodríguez-Sandoval, Eduardo
Effect of low-temperature storage time on rejected green banana for flour production

Revista Facultad Nacional de Agronomía Medellín, vol.
76, no. 3, 2023, September-December, pp. 10517-10526
Facultad de Ciencias Agrarias - Universidad Nacional de Colombia

DOI: <https://doi.org/10.15446/rfnam.v76n3.105789>

Available in: <https://www.redalyc.org/articulo.oa?id=179976349009>

- How to cite
- Complete issue
- More information about this article
- Journal's webpage in redalyc.org

UNAM  redalyc.org

Scientific Information System Redalyc

Network of Scientific Journals from Latin America and the Caribbean, Spain and Portugal

Project academic non-profit, developed under the open access initiative

Effect of low-temperature storage time on rejected green banana for flour production

Efecto del tiempo de almacenamiento a baja temperatura en
banano verde de rechazo para la producción de harina

<https://doi.org/10.15446/rfnam.v76n3.105789>

Yamilé Jaramillo-Garcés¹, Miguel Sacchet-Pérez¹, Gustavo Manjarres-Pinzon¹, Katherine Manjarres-Pinzon¹,
Guillermo Correa-Londoño² and Eduardo Rodríguez-Sandoval^{2*}

ABSTRACT

Keywords:

Banana flour
Chilling injury
Enzymatic browning
Musa cavendish

Banana (*Musa* sp.) crops have one of the greatest economic impacts in Colombia, with an estimated production of 2.2 million tons in 2019. The aim of this study was to evaluate the effect of three anti-browning solutions: S1 (citric acid), S2 (citric acid + ascorbic acid), and S3 (citric acid + ascorbic acid + sodium metabisulfite) on the color, moisture, aw, pH, and acidity characteristics of flour from rejected green bananas. No significant differences were found ($P>0.05$). The values of a^* and b^* in all samples were in the grey zone. L^* and WI presented values close to 50, which could be defined as a flour in a medium range of clarity. The citric acid anti-browning solution was selected based on criteria such as cost and availability. The second part of the study assessed the effect of the storage time (1, 3, 5, 7, 9 and 11 days) at 7 °C on the color and texture of fresh bananas; and pH, instrumental, and sensory color of banana flour. There were differences noticeable for the human eye in the color (ΔE) of the peel from day 3 compared to day 1; while in the pulp, these changes were observed from day 7. Statistically significant differences in instrumental and sensory color properties of banana flour were observed after day 7 ($P<0.05$). The maximum storage time at 7 °C of fresh green bananas to produce banana flour should not exceed 7 days because color may be affected.

RESUMEN

Palabras clave:

Harina de banano
Daño por frío
Pardeamiento enzimático
Musa cavendish

El banano (*Musa* sp.) es uno de los cultivos de mayor impacto económico en Colombia, se estima que para el 2019 se produjeron 2,2 millones de toneladas. El objetivo de este estudio fue evaluar el efecto de tres soluciones antipardeantes S1 (ácido cítrico), S2 (ácido cítrico + ácido ascórbico) y S3 (ácido cítrico + ácido ascórbico + metabisulfito de sodio) en las características de color, humedad, aw, pH, y la acidez de la harina de banana verde de rechazo. No se presentaron diferencias significativas ($P>0,05$). Los valores de a^* y b^* de todas las muestras se ubicaron en la zona gris. L^* y WI presentaron valores cercanos a 50, lo que podría definirse como una harina en un rango medio de claridad. La solución antipardeante con ácido cítrico fue seleccionada basándose en criterios como el costo y la facilidad de acceso. La segunda parte del estudio consistió en evaluar el efecto del tiempo (1, 3, 5, 7, 9 y 11 días) de almacenamiento a 7 °C de los bananos frescos sobre las propiedades de color y textura en la fruta, el pH; además del color instrumental y sensorial de la harina de banano. Se observaron diferencias evidentes para el ojo humano en el color (ΔE) de la cáscara a partir del día 3 con respecto al día 1; mientras que, en la pulpa estos cambios tan evidentes se observaron a partir del día 7. Las diferencias estadísticamente significativas de propiedades de color instrumental y sensorial en la harina de banano se observaron después del día 7 ($P<0,05$). El tiempo máximo de almacenamiento a 7 °C de los bananos verdes en fresco para la producción de harina de banano no debe ser superior a los 7 días porque se puede afectar su color.

¹Corporación Natural SIG. Grupo de Investigación en Biodiversidad, Territorio y Gente (BIOTEGE). Santa Marta, Magdalena, Colombia.

investigadoraextrusion@naturalsig.org , analistaextrusionbiotec@naturalsig.org , director@naturalsig.org , directoracientifica@naturalsig.org 

²Facultad de Ciencias Agrarias, Universidad Nacional de Colombia. Medellín, Colombia. gcorrea@unal.edu.co , edrodriguezs@unal.edu.co 

*Corresponding author

Bananas are one of the most consumed fruits in the world. In Colombia, this crop has one of the greatest impacts on the economy and is one of the most exported agricultural products, along with coffee and flowers (Minagricultura 2022). It is estimated that 2.2 million tons were produced in 2019, a figure that placed the country as the ninth largest producer in the world and the fifth largest exporter of this fruit after Ecuador, the Philippines, Guatemala, and Costa Rica, thus supplying one tenth of the export market (Andersen et al. 2020; Minagricultura 2020). According to the Ministry of Agriculture and Rural Development (MADR), the departments of Antioquia, Magdalena, and La Guajira are the main producers of banana, and 86% of their production is exported (Minagricultura 2020). Andersen et al. (2020) estimate that 1.75 million tons were exported, and it generated approximately 155,000 direct and indirect jobs.

The cavendish variety is one of the most produced and marketed in the world. It is also an important product of international trade (Kuan et al. 2015; Padhi and Dwivedi 2022). In nutritional terms, bananas stand out as a source of minerals, vitamins, carbohydrates, flavonoids, phenolic compounds, among others (Singh et al. 2018). However, this fruit is climacteric, thus perishable, and prone to post-harvest loss (Odetayo et al. 2022). Different investigations have been developed to mitigate these losses, so that green bananas can be used, specifically rejected ones, i.e., those that do not meet the standards of international markets such as variety, number, and size of fingers per bunch, color, appearance, diameter, packaging, and phytosanitary conditions (Sartori and Menegalli 2016; Stanley 2017).

One way to delay the biochemical processes of biological material—like the production of ethylene in climacteric fruits—is storage at low temperatures, although it can damage the structure of the plant material, which is known as chilling injury (Tian et al. 2022). In the case of bananas, the physiological damage occurs below 12 °C and worsens as the temperature decreases. Among the undesirable effects, color changes in the shell (discoloration and brown spots) caused by polyphenol oxidase (PPO)—an enzyme responsible for browning—and an impediment in the normal maturation process have been reported (Tian et al. 2022). Moreover, other possible damages during

storage due to mechanical and low moisture effects should be considered (Kader 2022).

Different by-products have been developed from rejected bananas to give them an added value, e.g., syrup, precooked products, dried banana, flour, and powder obtained by different technologies for food and pharmaceutical applications (Singh et al. 2018). Furthermore, green banana flour has gained greater interest due to its functional properties. However, some unfavorable reactions such as enzymatic browning occur during the flour production process. It is a biochemical reaction that occurs naturally in foods and affects especially fruits because the color of their pulp becomes dark. This leads to unwanted quality, sensory, and nutritional defects in the final product (Anyasi et al. 2017). The PPO enzyme, responsible for that reaction, acts on the phenolic compounds and oxidizes them to quinones. Subsequently, the latter are polymerized to form a relatively insoluble brown pigment known as melanin (Moon et al. 2020). Precisely, one of the challenges faced by the banana processing industry is to avoid the enzymatic browning that affects the pulp once the shell is removed (Anyasi et al. 2015).

Currently, there are various methods to control, reduce, or inhibit enzymatic browning. The most used physical methods are oxygen reduction and modified atmospheres, coating films, and inactivation of enzymes by heating, e.g., blanching (Dávila et al. 2016). Chemical methods have specialized in the use of substances that, according to their active ingredient, focus on the inhibition of the enzyme, oxygen, or formed products: acidulants reduce the pH of the food, therefore, the enzymatic action; sulfites delay the rate of melanin formation, thus reducing quinones to diphenols; antioxidants react with oxygen to prevent the oxidation of phenolic compounds; and chelating agents form complexes with the copper oxide present in PPO (Moon et al. 2020; Yupangui Tenesaca 2016).

The advantages of physical methods to avoid enzymatic browning are the homogenization of food treatment and the possibility of modulating process conditions. Some disadvantages are alteration of the consistency of the treated product, sometimes giving a cooked flavor, generating losses of nutrients, and resulting in a decreased weight of the product. Moreover, the effectiveness of

chemical methods depends on environmental factors such as pH, water activity (aw), temperature, light, and composition of the atmosphere, and are limited by the presence of the cuticle. The advantages of these methods are quickly and effectively inhibiting enzymatic browning, they can be applied to a variety of fruits, are often readily available and relatively inexpensive compared to other methods, and do not cause noticeable changes in the taste, aroma, or texture of fruits when used in suitable concentrations. Despite these advantages, it is important to note that the use of chemical inhibitors should be regulated to ensure food safety and minimize any potential adverse effects (Moon et al. 2020).

Ascorbic acid and citric acid are among the most common agents to inhibit enzymatic browning, alone or in combination. They are Generally Recognized as Safe (GRAS), and their use is less restricted (Anyasi et al. 2015; Wang et al. 2014). It has also been determined that the use of sulphites prevents banana pulp from browning and enables obtaining a clearer flour with greater acceptability by the consumer (Salazar et al. 2022). However, their use is more limited due to their toxicity (Ojeda et al. 2020). The aim of this study was to evaluate the influence of pretreatments with anti-browning solutions based on ascorbic acid, citric acid, and sodium metabisulfite, and the storage time of rejected green banana fruits at 7 °C on the color, firmness, moisture, aw, pH, acidity, and sensory color of banana flour.

MATERIALS AND METHODS

Location

The plant material used to produce the flour was rejected green banana (*Musa cavendish*) from the department of Magdalena (Colombia), municipalities of Aracataca, Ciénaga, and Zona Bananera, specifically from the Gran Vía area (Latitude 10° 50'47.336"N, Longitude 74° 8' 30.477"W) and Santa Rosalía (Latitude 10° 49'45.672"N, Longitude 74° 7' 26.297"W). Their maturity stages were 1 and 2 (green) (Kader 2022).

Preparation of plant material

The bunches were harvested between 10 and 12 weeks, taking into account the harvest age criteria for banana exports. Bunches older than 12 weeks cannot be exported because by the time this product reaches the destination country, they will be more ripe than normal and could

even have black spots (Alonso-Ugaglia et al. 2022). Furthermore, rejected bananas are not suitable for export due to the high-quality standards required by importers. The most outstanding characteristics of rejected bananas are low weight, presence of spots, physical damage and scars higher than 1%, fruit length less than 22 cm, and fruit diameter less than 3.5 cm (Vásquez-Castillo et al. 2019). The cutting process was carried out with the help of tapes placed during the taping process. When the order to cut a certain color of tape was given at first, only 25% is cut; the following week, 50%; and the last week, the remaining 25% (Alonso-Ugaglia et al. 2022).

Food-grade detergent and organic acid-based disinfectant (1% Acid-tech solution) were used for cleaning and disinfection. The following substances were used for pretreatment with anti-browning solutions: citric acid and ascorbic acid powder (Bell Chem, Medellín, Colombia), sodium metabisulfite powder (Químicos JM, Medellín, Colombia), reactive-grade phenolphthalein (Chemi, Milán, Italy), and sodium hydroxide (NaOH) pearls (Panreac, Darmstadt, Germany).

Rejected green banana fruits were transported from Santa Marta to Medellín by air at room temperature, packed in cardboard boxes, and properly arranged inside the box to be processed at Universidad Nacional de Colombia. The transportation time of the raw material was less than 12 h. Upon arrival, they were washed and disinfected. Subsequently, they were stored at 7 °C to delay the ripening process until they were used in flour preparation. During the pre-climacteric period, mature green fruit has a low basal respiration rate and ethylene production is almost undetectable. This period is also called "Green Life" (GL). The high sensitivity of the banana fruit to the duration and intensity of low temperatures could provoke chilling injury. The suitable storage GL is 35 days at 13 °C (Brat et al. 2020). However, this study was intended to evaluate the lowest temperature possible to verify its effect on the quality traits of banana flour; it was set at 7 °C. Studies have been carried out previously storing banana fruit at 7 and 9 °C (Chen et al. 2022; Othman et al. 2021).

Preparation of immersion solutions (Pretreatment)

For banana pre-treatment, anti-browning solutions (S1, S2, and S3) were prepared using citric acid, ascorbic acid, and sodium metabisulfite, as specified in Table 1. The

methodology employed to prepare them was taken from Cortés et al. (2013). Each experimental unit consisted of 288 g of 5 mm-thick slices of green banana, which were immersed for 10 min in 1 L of anti-browning solution (S1, S2, and S3).

Obtaining green banana flour

The rejected green banana was processed 3 days after the banana was harvested. Bananas were manually peeled

and then chopped into 5 mm-thick slices, using manual mandolins. The slices were immediately immersed in the anti-browning solution for 10 min. Subsequently, they were dried at 55 °C for 15 h in a forced convection oven (Memmert 750, Germany) and then ground in a blade mill (IKA MF 10 Basic, USA) to obtain the flour, which was packed in No. 12 metalized pet resealable bags (Alico, Colombia). They were stored at room temperature in a cool, dry place for further analysis.

Table 1. Anti-browning solutions.

Immersion solution	S1	S2	S3
Citric acid	50 mg 100 g ⁻¹ sample	50 mg 100 g ⁻¹ sample	50 mg 100 g ⁻¹ sample
Ascorbic acid		90 mg 100 g ⁻¹ sample	90 mg 100 g ⁻¹ sample
Sodium metabisulfite			500 ppm of the solution

Physicochemical characterization of green banana flour

The color was determined by instrumental measurement with a colorimeter (Chroma Meter CR-400/410, Japan) using the CIELAB color scale with the parameters L* (brightness), a* (red/green), and b* (yellow/blue) (Vélez-Urbe et al. 2023). Measurements were made in triplicate using Illuminant D65. The chromaticity parameters (C), hue angle (°H), and whiteness index (WI) were calculated. The pH was measured following the methodology described by AOAC 943.02 (AOAC 1997); titratable acidity (Padhi and Dwivedi 2022) with some modifications; water activity (aw) by modified AOAC 978.18 (AOAC 1997), moisture by AOAC 925.10 (AOAC 1997). The properties of the banana flours used in these treatments were compared to commercial banana flour (Harina de Cambur verde, Artesanos fit, Trujillo, Venezuela).

Evaluation of storage

The rejected green bananas' storage was evaluated on days 1, 3, 5, 7, 9 and 11. Color and firmness tests were carried out on both the shell and the pulp of the fresh fruits. In addition to the flour obtained, the color and pH parameters were evaluated under the aforementioned methodologies. Mechanical characterization was performed using the firmness test (Sanaeifar et al. 2016). It was determined in triplicate on a texture analyzer (Stable Micro System, TA-Xt2i) at three points. A firmness test was performed on bananas' shells and pulp. The firmness of

the samples was determined by a one-way penetration test, using a 2 mm diameter stainless steel cylindrical shaft and a load cell 50 kg. The operating parameters for the firmness test were pre-test speed, 2 mm s⁻¹; test speed, 2 mm s⁻¹; post-test speed, 2 mm s⁻¹; and penetration distance, 20 mm. The color sensory analysis was carried out by a triangular test for sensory differentiation according to ISO 10399:2017 (ISO - International Standards Organization 2017) to a group of 40 selected panelists. They were presented with three samples—two from the same treatment and one different—and asked to identify the sample that had a different color among the three samples.

Statistical analysis

The effect of the anti-browning solution (S1, S2, and S3) on the physicochemical and color properties of processed banana flour, and the effect of storage time of the rejected green bananas (days 1, 3, 5, 7, 9, and 11) on the flour produced from it were analyzed by one-way factorial design. Means were assessed by a Tukey multiple comparison test with a significance level $\alpha=0.05$ using the R statistical software (R Core Team 2022).

RESULTS AND DISCUSSION

Anti-browning solution

The effect of anti-browning solutions on physicochemical properties and CIELAB color coordinates (L*, a*, and b*) are shown in Table 2. The physicochemical and color properties of banana flour were not affected by pretreatment with S1,

S2, and S3 solutions. The parameters in the chromatic plane a^* and b^* of all samples are in the grey zone. L^* is a parameter associated with the clarity of the sample; in general, the results obtained in this research show values close to 50, which could be defined as a flour in a medium range of clarity. The WI is a parameter derived from the

combination of luminosity and yellow/blue (b^*) in a single term (Pathare et al. 2013). Therefore, when obtaining low values of L^* and b^* , the WI was not high. However, when comparing these results with a commercial flour, more relevant differences are observed in parameters such as L^* and WI, which are lower.

Table 2. Effect of the anti-browning solution on color parameters and physicochemical properties of banana flour.

Solution	Variable				
	L^*	a^*	b^*	C	$^{\circ}H$
S1	44.77±0.18 ^a	1.56±0.34 ^a	8.69±0.21 ^a	8.83±0.26 ^a	79.86±1.92 ^a
S2	45.60±0.80 ^a	1.50±0.21 ^a	9.26±0.50 ^a	9.38±0.46 ^a	80.78±1.75 ^a
S3	49.50±2.99 ^a	0.94±0.43 ^a	9.51±0.29 ^a	9.56±0.24 ^a	84.30±2.73 ^a
Commercial flour	36.85±2.40	1.46±0.14	7.70±0.17	7.84±0.19	79.30±0.87

Solution	Variable				
	WI	Moisture %	a_w	pH	Acidity**
S1	44.07±0.14 ^a	6.29±1.12 ^a	0.166±0.045 ^a	5.4±0.0 ^a	0.16±0.05 ^a
S2	44.80±0.72 ^a	6.24±1.14 ^a	0.168±0.037 ^a	5.3±0.0 ^a	0.20±0.00 ^a
S3	48.60±2.98 ^a	6.26±1.07 ^a	0.175±0.035 ^a	5.2±0.1 ^a	0.20±0.00 ^a
Commercial flour	36.36±2.37	10.56±0.15	0.459±0.06	5.9±0.0	0.13±0.03

The means of pretreatments with a common letter in a column do not differ significantly at a significance level $\alpha=0.05$, according to Tukey's DSH test. **Acidity expressed as malic acid.

The moisture content and water activity (a_w) properties in powdered products are critical, as they can affect other physical and chemical properties of food. In addition, they are key for shelf life and stability (Savlak et al. 2016). The moisture content found in green banana flours from Magdalena is within the percentages allowed in NTC 2799 (moisture<10%) (ICONTEC 2020). The results obtained are higher than those reported by Khoozani et al. (2019), who showed a moisture content in dried banana flour of 5.09, 4.56, and 4.46% at temperatures of 50, 80, and, 110 °C, respectively, and a_w values of 0.25, 0.34, and 0.39 for the same temperatures—higher than those obtained in this experiment. Campuzano et al. (2018) evaluated the moisture content in cavendish banana flour (*Musa acuminata* AAA) from Ecuador at maturation stage one and obtained a higher moisture value of 10.88±0.17 g 100 g⁻¹. Meanwhile, Savlak et al. (2016) evaluated moisture, a_w , and pH in “Dwarf cavendish” green banana flour (*Musa* spp. AAA) from Turkey and reported a moisture value of 9.07±0.35%, a_w of 0.42±0.02, and pH of 5.66±0.01—higher than those presented in this study and similar to those of commercial flour. Solutions with only organic acids (S1 and S2) in some cases tend to be slightly more

acidic because of the nature of the substances employed in the pretreatment; however, no statistically significant differences are reported between samples. The literature reports data that tend towards neutrality with pH=6.12 and 0.11% for acidity (Padhi and Dwivedi 2022).

As there were no significant differences among the anti-browning solutions to produce banana flour in the proposed design, the solution was selected considering other criteria such as the most used anti-browning agent, its adverse effects on health, and costs. Although all the agents used are considered GRAS, a positive effect of anti-browning agents has been observed when obtaining banana flours, e.g., citric acid used at different concentrations (Chang et al. 2022; Savlak et al. 2016). In addition, Sarpong et al. (2018) report the positive effect of citric acid on the inhibition of enzymes such as polyphenol oxidase. Ascorbic acid, in addition to inhibiting polyphenol oxidase, can repress the yield of o-quinones in diphenols (Homaida et al. 2017). Ali et al. (2015) also observed that a lower concentration of ascorbic acid acted as an inhibitor of enzymes, but a higher concentration only reduced the formation of quinones.

Sulfur dioxides or their salts, such as sodium metabisulfite, have also been applied due to their positive effect as anti-browning agents when obtaining banana flours (Padhi and Dwivedi 2022; Salazar et al. 2022). Although sodium metabisulfite has been widely used in the food industry due to its ability to prevent enzymatic and non-enzymatic browning and microbial growth, and as a bleaching agent that helps preserve flavor, texture, and color in food, it is regulated by INVIMA (maximum 1,500 mg kg⁻¹) in Colombia and there are some doubts about the use of sulphites in food products due to possible health effects (Ojeda et al. 2020).

Citric acid was selected as the best anti-browning agent considering that approximately 15,000, 1,500, and 204 t of citric acid, ascorbic acid, and sulfites were imported in 2021, which indicates increased availability of the first one, and their import costs were approximately 1.29, 641, and 2.13 USD kg⁻¹, respectively (MinCIT 2022); citric acid having the lower import cost.

Storage time

Once the anti-browning solution (S1) was selected, the fruit's storage time at low temperatures to obtain flour was evaluated using the color and firmness parameters of fresh green banana with the peel and in the pulp. Results are shown in Table 3. There are no significant changes in the peel firmness during storage with an average value of 13 to 14.5 N. Moreover, an increase in the pulp firmness was observed on the 3rd day of storage, and then it remained with values close to 6 N. The texture changes in the pulp can be due to several factors like the contributions of starch hydrolysis, the enzymatic disruption of the cell wall structure, the water migration from the banana peel to the pulp, fruit mechanical damage, fruit physiological problems, or poor post-harvest handling (Sinanoglou et al. 2023).

The hue angle or tone (°H) in vegetables expresses the color variation, which takes 0° for red, 90° for yellow, and 180° for green. Although this parameter gradually changes

Table 3. Effect of fresh banana storage time on color and firmness parameters.

Parameter	Part of the banana	DAY					
		1	3	5	7	9	11
L*	Peel	54.01±1.92 ^a	53.62±1.83 ^a	54.08±3.61 ^a	53.22±1.71 ^a	54.00±4.73 ^a	55.48±3.51 ^a
	Pulp	83.31±1.15 ^b	82.91±0.83 ^b	84.54±1.38 ^b	88.21±1.37 ^a	86.91±1.40 ^a	87.96±1.41 ^a
a*	Peel	-15.99±0.88 ^c	-17.1±0.75 ^c	-9.25±2.75 ^a	-11.94±1.25 ^b	-11.93±2.01 ^b	-13.32±0.92 ^b
	Pulp	-1.21±0.17 ^{ab}	-1.21±0.12 ^{ab}	-1.05±0.25 ^a	-1.24±0.12 ^{ab}	-1.54±0.29 ^c	-1.36±0.21 ^{bc}
b*	Peel	30.07±1.54 ^b	34.31±1.29 ^a	29.64±1.76 ^b	30.46±1.69 ^b	30.30±3.35 ^b	33.24±1.20 ^a
	Pulp	19.56±1.09 ^{bc}	18.17±0.92 ^c	19.79±1.10 ^{bc}	19.54±1.93 ^{bc}	22.13±1.23 ^a	20.97±0.95 ^{ab}
C	Peel	34.06±1.64 ^{bc}	38.33±1.45 ^a	31.12±2.43 ^c	32.73±1.94 ^{bc}	32.58±3.76 ^c	35.81±1.39 ^{ab}
	Pulp	19.59±1.08 ^{bc}	18.21±0.92 ^c	19.82±1.10 ^{bc}	19.58±1.93 ^{bc}	22.18±1.22 ^a	21.02±0.95 ^{ab}
°H	Peel	118.01±1.11 ^a	116.49±0.52 ^a	107.07±4.09 ^c	111.37±1.45 ^b	111.42±1.80 ^b	111.82±0.96 ^b
	Pulp	93.56±0.64 ^{ab}	93.81±0.50 ^{ab}	93.05±0.77 ^b	93.67±0.44 ^{ab}	94.00±0.80 ^a	93.70±0.57 ^{ab}
WI	Peel	42.73±1.32 ^a	39.81±1.75 ^b	44.41±2.19 ^a	42.86±0.57 ^a	43.38±2.21 ^a	42.83±3.08 ^a
	Pulp	74.24±1.13 ^b	75.02±1.00 ^{ab}	74.85±1.53 ^b	77.14±2.30 ^a	74.22±1.40 ^b	75.76±1.46 ^{ab}
ΔE	Peel	-	4.40	6.75	4.15	4.06	4.40
	Pulp	-	1.45	1.26	4.90	4.44	4.86
Firmness (N)	Peel	14.32±1.34 ^a	13.07±1.31 ^a	14.57±3.01 ^a	13.47±2.22 ^a	13.26±2.40 ^a	13.65±1.55 ^a
	Pulp	5.22±0.40 ^b	6.28±0.52 ^a	5.66±0.97 ^{ab}	5.51±0.44 ^{ab}	5.79±0.45 ^{ab}	5.90±0.60 ^{ab}

The means of properties with a common letter in a row do not differ significantly at a significance level $\alpha=0.05$, according to Tukey's DSH test. Parameter ΔE was calculated based on day 1.

over time from green to yellow in bananas (Jaiswal et al. 2014), in this experiment, it remained green due to the

low storage temperature that delayed ethylene production (Facundo et al. 2015). Values close to 90° in the pulp

show a tendency to yellow. According to the ΔE in the banana peel, it was observed that the color difference on days 3, 5, 7, 9, and 11 is obvious to the human eye. Moreover, in banana pulp, the color difference in days 3 and 5 is smaller and could be appreciated by the human eye depending on the tone with respect to day 1. From day 7 of storage, changes in color with respect to day 1 are easily perceived by the human eye (Goswami et al. 2015).

Facundo et al. (2015) studied the influence of low-temperature storage on skin color and carotenoid content in two banana cultivars (cv. Prata and cv. Nanicao). They found that bananas stored at temperatures of 10 and 13 °C did not show changes in color and it was maintained until 15 days. Figure 1 shows that the color

in the banana peel remained green during the 11 days of storage, although at day 5 some brown colorations began to appear. These results are similar to those reported by Wang et al. (2021), who observed some brown spots from day 4 of storage at 7 °C that may be associated with cold damage. It affects the parameters L^* , C , and $^{\circ}H$. During the 11 days, it was also found that the luminosity (L^*) of the banana peel did not present significant differences, while significant changes were observed in the pulp ($P<0.05$) from day 7. The color changes of the banana pulp could be attributed to increases in the moisture content and oxygen penetration to the pulp during the storage period. Moreover, the redness (a^*) fluctuations of the banana pulp could be associated with a differentiation of the total carotenoid-content during ripening and the brown spots on the peel (Sinanoglou et al. 2023).



Figure 1. Evolution of bananas in cold storage over time.

The effect of the storage time (1, 3, 5, 7, 9, and 11 day) on the fresh banana fruit to produce banana flour is shown in Table 4. In products such as flour, color is one of the sensory attributes that impacts the evaluation and acquisition of food for both the consumer and the food

industries. Thus, whiter flour improves acceptance and interest, since when incorporated as an ingredient in products, it will cause few changes in the final color. When the yellow component (b^*) or the green component (a^*) predominates on the values of the coordinates a^* and b^* ,

Table 4. Parameters of pH and color of banana flour.

Day	Parameter							$\Delta E'$
	pH	L^*	a^*	b^*	C	$^{\circ}H$	WI	
1	5.57±0.01 ^e	52.46±1.48 ^c	1.45±0.06 ^{cd}	8.52±0.42 ^b	8.65±0.42 ^b	80.32±0.13 ^{cd}	51.68±1.38 ^c	-
3	5.68±0.0 ^a	52.97±0.88 ^c	1.58±0.05 ^{bc}	8.83±0.21 ^b	8.97±0.21 ^b	79.87±0.14 ^d	52.12±0.82 ^c	0.60
5	5.64±0.00 ^{bc}	51.83±1.26 ^c	1.48±0.02 ^{bc}	8.89±0.22 ^b	9.01±0.22 ^b	80.52±0.12 ^c	50.99±1.20 ^c	0.73
7	5.63±0.01 ^{cd}	53.53±1.12 ^c	1.36±0.04 ^d	9.42±0.20 ^{ab}	9.51±0.20 ^{ab}	81.78±0.14 ^a	52.57±1.05 ^c	1.40
9	5.62±0.01 ^d	64.69±2.70 ^a	1.62±0.08 ^b	10.37±0.60 ^a	10.49±0.61 ^a	81.12±0.08 ^b	63.14±2.42 ^a	12.37
11	5.65±0.01 ^b	59.11±2.64 ^b	1.94±0.03 ^a	9.35±0.34 ^b	9.55±0.34 ^{ab}	78.27±0.34 ^e	58.00±2.50 ^b	6.72

The means of pretreatments with a common letter in a column do not differ significantly at a significance level $\alpha=0.05$, according to Tukey's DSH test. Parameter $\Delta E'$ was calculated based on day 1.

flour with tendencies to a darker or lighter yellow color is obtained (Bezerra et al. 2013).

The L^* and WI values showed no statistically significant differences ($P>0.05$) until day 7 of storage with respect to day 1. However, although they are slightly higher than those found in the first part of this experiment, in the chromatic plane, the samples continue to be in the gray area with medium luminosity and whiteness. Lower L^* values can be attributed to the oven drying process (Savlak et al. 2016). Additionally, the browning process is known to occur due to the presence of four components: oxygen, oxidizing enzyme (polyphenol oxidase), a metal ion (copper), and a suitable substrate (phenolic substrate) (Moon et al. 2020). Consequently, it would not be possible to attribute browning in flour only to the action of polyphenol oxidase. Regarding the color differences with respect to day 1, it is observed that the flours processed on days 3 and 5 are classified as non-perceptible ($\Delta E^* < 1$). On day 7 the changes are minor and could be perceived by the human eye depending on the tone of the sample on day 1 ($1 < \Delta E^* < 3$). From day 9 of storage, there would be obvious changes for the human eye ($\Delta E^* > 3$) (Goswami et al. 2015).

Sensory color

Sensory analysis encompasses a set of techniques for correct judgment of human responses to food and tracks

the potential bias effects of fraud, brand identity, and quality that influence consumer perception. Since it is a measurement science, it seeks—like other instrumental techniques—the accuracy, sensitivity, and prevention of false-positive results (Drake et al. 2023). Consumers generally evaluate the quality of a product based on its appearance and color; then, through this additional evaluation of color by instrumental methods, it intended to find out if a group of 40 panelists could determine the color differences between banana flours made on days 3, 5, 7, 9, and 11 with respect to day 1. Therefore, a triangular test was carried out in which a series of correct choices, beyond what is expected, is considered evidence of a discernible difference between samples (Mihafu et al. 2020). The results obtained for each day are presented in Table 5. The data were taken from a binomial statistical table, which establishes that when more than 19 panelists out of 40 respond correctly, the samples present statistically significant differences ($P<0.05$) (International Standards Organization- ISO 2017). The sensory panel of the triangular test showed a significant difference ($P<0.05$) between the banana flour made on days 9 and 11 of storage and that made on day 1, with a total of 20 and 24 correct answers, respectively. The color results of the flour at the sensory level confirmed what was obtained at the instrumental level, i.e., the color differences are more obvious for the human eye from day 9 of fresh green banana storage.

Table 5. Sensory color.

Day	Correct answers	P
3	10	0.9034
5	14	0.4703
7	9	0.9517
9	20	0.0214
11	24	0.0005

CONCLUSIONS

The contribution of this research indicates the anti-browning solutions used in this study do not have a significant effect on the color, moisture, aw, pH, and acidity of banana flour. Therefore, it is beneficial for the industry to select them appropriately based on their availability and cost. The use of citric acid is recommended as an anti-browning solution to produce banana flour due to its wide application in this field,

low cost compared to the other two solutions evaluated, availability in the local market, and it is generally recognized as safe. Furthermore, this research corroborates the findings of other previous studies that have employed these chemical agents, obtaining similar results in line with the standards established by the corresponding regulations. Moreover, it is crucial to have knowledge of the maximum storage time of the fruit in the food industrial field to ensure

flour production that does not exhibit alterations in terms of taste, color, or poor texture, while avoiding the loss of essential nutrients. These factors can directly impact production costs and process profitability. According to the literature, the suitable storage temperature for green bananas should be close to 13 °C; however, they were stored at 7 °C to evaluate a limited storage temperature for this climacteric fruit. The maximum storage time of rejected fresh green banana fruits at 7 °C to produce banana flour should not exceed 7 days because their color may be affected. It is suggested that future research delve further into the combination of physical treatments along with the use of anti-browning agents, or even the use of natural extracts as alternatives to these chemical agents. Furthermore, the effect of pretreatment with citric acid should be evaluated in pasting, thermal, and techno-functional properties of banana flour. Thus, innovative approaches can be identified to optimize the quality and preservation of banana flour, and both the industry and consumers could profit from it.

ACKNOWLEDGMENTS

To Tecniban project BPIN code 2020000100698 and Hermes code 51045, Corporación Natural SIG, and Universidad Nacional de Colombia - Medellín Headquarters.

REFERENCES

- Ali HM, El-Gizawy AM, El-Bassiouny REI and Saleh MA (2015) Browning inhibition mechanisms by cysteine, ascorbic acid and citric acid, and identifying PPO-catechol-cysteine reaction products. *Journal of Food Science and Technology* 52(6): 3651–3659. <https://doi.org/10.1007/s13197-014-1437-0>
- Alonso-Ugaglia A, Prieto AV and Díaz EA (2022) Construcción de un prototipo para el análisis de la sostenibilidad de los sistemas agrícolas en el Magdalena, Colombia. El caso del sector bananero. *Revista CIRIEC Costa Rica* 1(1): 671-683. <https://revistasecauned.com/index.php/ciriec/article/view/115>
- Andersen LE, Anker R and Anker M (2020) Living wage report caribbean coast of Colombia. Series 1. Report 20. In: *Global Living Wage Coalition*. https://www.globallivingwage.org/wp-content/uploads/2020/06/LW-Report_Colombia_2019_en.pdf accessed: October 2022.
- Anyasi TA, Jideani AIO and McHau GRA (2015) Effect of organic acid pretreatment on some physical, functional and antioxidant properties of flour obtained from three unripe banana cultivars. *Food Chemistry* 172: 515–522. <https://doi.org/10.1016/j.foodchem.2014.09.120>
- Anyasi TA, Jideani AI and Mchau GR (2017) Effects of organic acid pretreatment on microstructure, functional and thermal properties of unripe banana flour. *Food Measure* 11: 99–110. <https://doi.org/10.1007/s11694-016-9376-2>
- Brat P, Bugaud C, Guillermet C and Salmon F (2020) Review of banana green life throughout the food chain: From auto-catalytic induction to the optimisation of shipping and storage conditions. *Scientia Horticulturae* 262: 109054. <https://doi.org/10.1016/j.scienta.2019.109054>
- Bezerra CV, Amante ER, de Oliveira DC et al (2013) Green banana (*Musa cavendishii*) flour obtained in spouted bed - Effect of drying on physico-chemical, functional and morphological characteristics of the starch. *Industrial Crops and Products* 41(1): 241–249. <https://doi.org/10.1016/j.indcrop.2012.04.035>
- Campuzano A, Rosell CM and Cornejo F (2018) Physicochemical and nutritional characteristics of banana flour during ripening. *Food Chemistry* 256: 11–17. <https://doi.org/10.1016/j.foodchem.2018.02.113>
- Chang L, Yang M, Zhao N et al (2022) Structural, physicochemical, antioxidant and in vitro digestibility properties of banana flours from different banana varieties (*Musa* spp.). *Food Bioscience* 47: 101624. <https://doi.org/10.1016/j.fbio.2022.101624>
- Chen BK, Chang CK, Cheng KC, Hou CY et al (2022) Using the response surface methodology to establish the optimal conditions for preserving bananas (*Musa acuminata*) in a pulsed electric field and to decrease browning induced by storage at a low temperature. *Food Packaging and Shelf Life* 31: 100804. <https://doi.org/10.1016/j.fpsl.2021.100804>
- Cortés RM, Dávila M and Gil JH (2013) Impregnation solution influence on the pulp color of plantains (*Musa paradisiaca*). *Revista Facultad Nacional de Agronomía Medellín* 66(1): 6949–6958. http://www.scielo.org.co/scielo.php?script=sci_arttext&pid=S0304-28472013000100012&lng=en&nrm=iso
- Dávila M, Cortés RM and Gil JH (2016) Cambios físicos y fisicoquímicos durante el almacenamiento en plátano impregnado al vacío con soluciones antioxidantes. *Biotechnología en el Sector Agropecuario y Agroindustrial* 14(2): 125–134.
- Drake MA, Watson ME and Liu Y (2023) Sensory analysis and consumer preference: best practices. *Annual Review of Food Science and Technology* 14: 427–448.
- Facundo HVDV, Gurak PD, Mercadante AZ, Lajolo FM and Cordenunsi BR (2015) Storage at low temperature differentially affects the colour and carotenoid composition of two cultivars of banana. *Food Chemistry* 170: 102–109. <https://doi.org/10.1016/j.foodchem.2014.08.069>
- Goswami D, Gupta RK, Mridula D, Sharma M and Tyagi SK (2015) Barnyard millet-based muffins: Physical, textural and sensory properties. *LWT* 64(1): 374–380. <https://doi.org/10.1016/j.lwt.2015.05.060>
- Homaida MA, Yan S and Yang H (2017) Effects of ethanol treatment on inhibiting fresh-cut sugarcane enzymatic browning and microbial growth. *LWT* 77: 8–14. <https://doi.org/10.1016/j.lwt.2016.10.063>
- ISO - International Standards Organization (2017) Sensory analysis — Methodology — Duo-trio test (ISO 10399:2017; p. 21).
- Jaiswal P, Jha SN, Kaur PP, Bhardwaj R, Singh AK and Wadhawan V (2014) Prediction of textural attributes using color values of banana (*Musa sapientum*) during ripening. *Journal of Food Science and Technology* 51: 1179–1184. <https://doi.org/10.1007/s13197-012-0614-2>
- Kader AA (2022) Recomendaciones para mantener la calidad postcosecha: Banano (Plátano). In: *Posharvest Center*. University of California.
- Khoozani AA, Bekhit AEDA and Birch J (2019) Effects of different drying conditions on the starch content, thermal properties and some of the physicochemical parameters of whole green banana flour.

International Journal of Biological Macromolecules 130: 938–946. <https://doi.org/10.1016/j.ijbiomac.2019.03.010>

Kuan CH, Ahmad SH, Son R, Yap ESP et al (2015) Influence of forced-air precooling time on the changes in quality attributes and consumer acceptance of *Musa* AAA Berangan. International Food Research Journal 22(5): 1864–1869. [http://www.ifrj.upm.edu.my/22%20\(05\)%202015/\(18\).pdf](http://www.ifrj.upm.edu.my/22%20(05)%202015/(18).pdf)

Mihafu FD, Issa JY and Kamiyango MW (2020) Implication of sensory evaluation and quality assessment in food product development: A review. Current Research in Nutrition and Food Science Journal 8(3): 690–702. <https://doi.org/10.12944/CRNFSJ.8.3.03>

MinCIT (2022) Informes de importaciones colombianas y balanza comercial. In: Ministerio de Comercio, Industria y Turismo. <https://www.mincit.gov.co/estudios-economicos/estadisticas-e-informes/informes-de-importaciones-colombianas-y-balanza-co-1-p.;consultado:> Octubre, 2022.

Minagricultura (2020) Cadena de banano. In: Ministerio de Agricultura y Desarrollo Rural. <https://sioc.minagricultura.gov.co/Banano/Documentos/2020-12-31%20Cifras%20Sectoriales.pdf>. Consultado: Octubre, 2022.

Minagricultura (2022) Exportaciones del sector agropecuario crecieron 30% y sumaron US\$4.023 millones a abril de 2022. In: Ministerio de Agricultura y Desarrollo Rural. [https://agronet.gov.co/Noticias/Paginas/Exportaciones-del-sector-agropecuario-crecieron-30-y-sumaron-US\\$4-023-millones-a-abril-de-2022.aspx](https://agronet.gov.co/Noticias/Paginas/Exportaciones-del-sector-agropecuario-crecieron-30-y-sumaron-US$4-023-millones-a-abril-de-2022.aspx). Consultado: Octubre, 2022.

Moon KM, Kwon EB, Lee B and Kim CY (2020) Recent trends in controlling the enzymatic browning of fruit and vegetable products. Molecules 25(12): 2754. <https://doi.org/10.3390/molecules25122754>

Odetayo T, Sithole L, Shezi S, Nomngongo P, Tesfay S and Ziphorah NN (2022) Effect of nanoparticle-enriched coatings on the shelf life of Cavendish bananas. Scientia Horticulturae 304: 111312. <https://doi.org/10.1016/j.scienta.2022.111312>

Ojeda GA, Sgroppo SC and Zartizky NE (2020) Fogging with antibrowning agents as an alternative to conventional immersion treatments to extend shelf life of mushrooms. International Journal of Food Science and Technology 55(2): 660–668.

Othman SH, Abdullah NA, Nordin N, Shah NNAK et al (2021) Shelf life extension of Saba banana: Effect of preparation, vacuum packaging, and storage temperature. Food Packaging and Shelf Life 28: 100667. <https://doi.org/10.1016/j.fpsl.2021.100667>

Padhi S and Dwivedi M (2022) Physico-chemical, structural, functional and powder flow properties of unripe green banana flour after the application of refractance window drying. Future Foods 5: 100101. <https://doi.org/10.1016/j.fufo.2021.100101>

Pathare PB, Opara UL and Al-Said FAJ (2013) Colour measurement and analysis in fresh and processed foods: A review. Food and Bioprocess Technology 6(1): 36–60. <https://doi.org/10.1007/s11947-012-0867-9>

Salazar D, Arancibia M, Lalaleo D, Rodríguez-Maecker R et al (2022) Physico-chemical properties and filmogenic aptitude for edible packaging of Ecuadorian discard green banana flours (*Musa acuminata* AAA). Food Hydrocolloids 122: 107048. <https://doi.org/10.1016/j.foodhyd.2021.107048>

Sanaeifar A, Mohtasebi SS, Ghasemi-Varnamkhasti M and Ahmadi H (2016) Application of MOS based electronic nose for the prediction

of banana quality properties. Measurement 82: 105–114. <https://doi.org/10.1016/j.measurement.2015.12.041>

Sarpong F, Yu X, Zhou C, Oteng-Darko P, Amenorfe LP et al (2018) Drying characteristic, enzyme inactivation and browning pigmentation kinetics of controlled humidity-convective drying of banana slices. Heat and Mass Transfer 54: 3117–3130. <https://doi.org/10.1007/s00231-018-2354-y>

Sartori T and Menegalli FC (2016) Development and characterization of unripe banana starch films incorporated with solid lipid microparticles containing ascorbic acid. Food Hydrocolloids 55: 210–219. <https://doi.org/10.1016/j.foodhyd.2015.11.018>

Savlak N, Türker B and Yeşilkanat N (2016) Effects of particle size distribution on some physical, chemical and functional properties of unripe banana flour. Food Chemistry 213: 180–186. <https://doi.org/10.1016/j.foodchem.2016.06.064>

Sinanoglou VJ, Tsiaka T, Aouant K, Mouka E, Ladika G et al (2023) Quality assessment of banana ripening stages by combining analytical methods and image analysis. Applied Sciences 13(6): 3533. <https://doi.org/10.3390/app13063533>

Singh R, Kaushik R and Gosewade S (2018) Bananas as underutilized fruit having huge potential as raw materials for food and non-food processing industries: A brief review. The Pharma Innovation Journal 7(6): 574–580.

Stanley R (2017) Final Report Commercial feasibility of banana waste utilisation in the processed food industry. In: Horticulture Innovation Australia Limited 2013. <https://www.horticulture.com.au/globalassets/laserfiche/assets/project-reports/ba09025/ba09025-final-report-341.pdf>. Accessed: October 2022.

Tian J, Xie S, Zhang P, Wang Q, Li J and Xu X (2022) Attenuation of postharvest peel browning and chilling injury of banana fruit by Astragalus polysaccharides. Postharvest Biology and Technology 184: 111783. <https://doi.org/10.1016/j.postharvbio.2021.111783>

Vásquez-Castillo W, Racines-Oliva M, Moncayo P, Viera W and Seraquive M (2019) Fruit Quality and Post-Harvest Losses of Organic Bananas (*Musa acuminata*) in Ecuador. Enfoque UTE 10(4): 57–66. <https://doi.org/10.29019/enfoque.v10n4.545>

Vélez-Urbe T, Orozco-Agudelo N, Manjarrés-Pinzón G, Manjarrés-Pinzón K et al (2023) Physicochemical, antioxidant, and technofunctional properties of mushroom (*Pleurotus* sp) flour obtained by hot air drying. DYNA 90(225): 85–94. <https://doi.org/10.15446/dyna.v90n225.106026>

Wang S, Lin T, Man G, Li H, Zhao L, Wu J and Liao X (2014) Effects of anti-browning combinations of ascorbic acid, citric acid, nitrogen and carbon dioxide on the quality of banana smoothies. Food and Bioprocess Technology 7(1): 161–173. <https://doi.org/10.1007/s11947-013-1107-7>

Wang Z, Pu H, Shan S, Zhang P, Li J et al (2021) Melatonin enhanced chilling tolerance and alleviated peel browning of banana fruit under low temperature storage. Postharvest Biology and Technology 179: 111571. <https://doi.org/10.1016/j.postharvbio.2021.111571>

Yupangui Tenesaca MG (2016) Métodos utilizados para evitar el pardeamiento enzimático y no enzimático en el puré de banano en la industria alimenticia. (Tesis de Pregrado) Programa de Ingeniería de Alimentos. Universidad Técnica de Machala. <http://repositorio.utmachala.edu.ec/bitstream/48000/7588/1/yupangui.pdf>. 27 p.