



DYNA

ISSN: 0012-7353

ISSN: 2346-2183

Universidad Nacional de Colombia

Silva, José Leôncio de Almeida; Duarte, Sergio Nascimento;
Silva, Demetrius David da; Miranda, Neyton de Oliveira
Reclamation of salinized soils due to excess of fertilizers: evaluation of leaching systems and equations
DYNA, vol. 86, no. 210, 2019, July-September, pp. 115-124
Universidad Nacional de Colombia

DOI: <https://doi.org/10.15446/dyna.v86n210.77391>

Available in: <https://www.redalyc.org/articulo.oa?id=49662789014>

- ▶ [How to cite](#)
- ▶ [Complete issue](#)
- ▶ [More information about this article](#)
- ▶ [Journal's webpage in redalyc.org](#)



Scientific Information System Redalyc

Network of Scientific Journals from Latin America and the Caribbean, Spain and Portugal

Project academic non-profit, developed under the open access initiative

Reclamation of salinized soils due to excess of fertilizers: evaluation of leaching systems and equations

José Leôncio de Almeida Silva ^a, Sergio Nascimento Duarte ^b, Demetrius David da Silva ^a & Neyton de Oliveira Miranda ^c

^a Department of Agricultural Engineering, Federal University of Viçosa (UFV), Viçosa, Brazil. jleoncio100@hotmail.com, demetrius.ufv@gmail.com

^b University of São Paulo - Luiz de Queiroz College of Agriculture (USP/ESALQ), Piracicaba, Brazil. snduarte@usp.br

^c Center for Agrarian Sciences, Universidade Federal Rural do Semi-Arido (UFERSA), Mossoró, Brazil. neyton@ufersa.edu.br

Received: January 22th, 2019. Received in revised form: June 20th, 2019. Accepted: July 4th, 2019.

Abstract

In regions with intense irrigation, the use of fertirrigation increases crop productivity, but excessive fertilizer application increases the risk of soil salinization. Therefore, this work used leaching equations to evaluate systems of remediation of soils salinized by excess fertilizers. The phases of the study were: salinization of soils in lysimeters, remediation of these soils, and measurement of salt concentrations in soils for comparison with estimates of empirical equations. The treatments combined soil remediation systems (continuous and intermittent) with five initial levels of soil salinity (2.0, 4.0, 6.0, 8.0, and 10.0 dS m⁻¹). The experimental design was randomized blocks with six replicates. The Volobuyev equation best represented the salinized soil remediation in relation to the results obtained experimentally. The equations tested showed better performance in the intermittent remediation system compared to the continuous system.

Keywords: salinization; irrigation management; leaching; fertirrigation.

Recuperación de suelos salinizados por exceso de fertilizantes: evaluación de sistemas de lixiviación y ecuaciones

Resumen

En las regiones con riego intenso, la fertirrigación aumenta la productividad de los cultivos, pero la aplicación excesiva de fertilizantes aumenta el riesgo de salinización del suelo. Por lo tanto, se utilizaron ecuaciones de lixiviación para evaluar sistemas de recuperación de suelos salinizados por exceso de fertilizantes. Las fases del estudio fueron: la salinización de los suelos en lisímetros, la recuperación de estos suelos y la medición de las concentraciones de sal en los suelos para la comparación con estimaciones de ecuaciones empíricas. Los tratamientos combinaron sistemas de recuperación del suelo (continuo e intermitente) en cinco niveles iniciales de salinidad del suelo (2,0; 4,0; 6,0; 8,0 y 10,0 dS m⁻¹). El diseño experimental fue de bloques al azar con seis repeticiones. La ecuación de Volobuyev representó mejor la remediación del suelo salinizado en relación con los resultados obtenidos experimentalmente. Las ecuaciones evaluadas mostraron un mejor desempeño en el sistema intermitente que en el sistema continuo.

Palabras clave: salinización; manejo de la irrigación; lixiviación; fertirrigación.

1. Introduction

In regions where irrigation is intensive, fertirrigation is a widely used practice as an alternative to conventional fertilization, aiming at increasing crop productivity. The technique aims at simultaneously meeting the water demand by the crop and supplying nutrients via irrigation water,

leaving the nutrients in soluble form and therefore, more quickly available. However, excessive application of fertilizers via fertirrigation may increase the risk of soil salinization [1].

The increase in soil salinity is usually related to the excessive use of fertilizers applied via irrigation water or the use of irrigation water from saline sources. In semiarid

regions, in order to minimize these problems, farmers often use the practice of leaching salts to deeper soil layers. However, in many cases the leaching water depths used are not sufficient to prevent the increase of the salt content in the crop root zone. In these situations, it is necessary to reduce the soil salinity to a level tolerated by the crop, by means of a reclamation leaching [2]. According to Hoffman [3], when the water is not strongly saline, so that during the crop cycle the soil salinity does not exceed its threshold, it is not necessary to carry out constant leaching. In this case, only maintenance flushing needs to be performed, at the end of the crop cycle.

According to the FAO, annual crop losses caused by extreme events due to water loss, erosion and salinization are estimated at 0.3%. If this problem increases at the current pace, a total reduction of more than 10% is expected by 2050 [4].

The volume of water required for reclamation leaching of a soil profile is calculated as a function of the initial soil salinity, the desired final salinity level, the type and depth of the soil to be reclaimed, the method of water application, and the salt concentration of the washing water [5].

Although many studies have been published with mathematical models to simulate the reclamation of saline soils, the amount of water used in the washing necessary for the reclamation of these soils is generally calculated using empirical relationships [6].

Due to the doubts still existing regarding the control of soil salinity and management, and the diverse models and formulas used to calculate leaching water depth, there is great variation in the amount of water recommended. In this context, this work examines the reclamation of soils salinized by excess fertilizers and the different leaching systems and equations to determine the corresponding parameters.

2. Material and methods

2.1. Location and preparation of the experiment

The field experiment was carried out at the Department of Biosystems Engineering of the "Luiz de Queiroz" School of Agriculture of the University of São Paulo (ESALQ/USP), located in Piracicaba, SP (22° 42' S, 47° 37' W and 540 m a.m.s.l), using tubular lysimeters made of concrete, waterproofed inside and with a top surface protected with plastic. Their dimensions were 1.2 m in height and 0.5 m in diameter, totaling 0.20 m² of cross-sectional surface area and 240 liters of useful volume.

According to the classification of Koppen, the climate of the region is type CWa, meaning tropical humid, with three dry months (from June to August) and occurrences of summer rains and winter droughts. The average temperature of the warmer month is higher than 22 °C, and in the coldest month it is below 18 °C.

The study consisted of three steps: 1) salinization of soils contained in the lysimeters; 2) reclamation of salinized soils; and 3) measurement of salt concentrations in the soils after the desalination procedure. For this task, we considered intermittent and continuous reclamation systems and compared these concentrations with those calculated by the

empirical formulas.

The first step was based on the use of artificial salinization curves for "Sertãozinho" Yellow Red Latosol, obtained in a previous experiment carried out in 8 liter pots. In the second step, we applied percolation water depths for the washing and reclamation of the salinized soils contained in the tubular lysimeters. In the last step, we applied empirical equations, obtained from technical and scientific publications, to estimate the concentrations of salts remaining in the soil solution after the application of the leaching depths in the intermittent and continuous systems. The concentrations predicted by the equations were compared to the actual concentrations measured in the soil in the lysimeters.

2.2. Construction of the salinization curve (previous experiment)

To find the relationship between the electrical conductivity of the solution (ECs) after the salinization and the total of salts to be applied, the desired proportions of salts were dissolved, initially taking as reference the equation proposed by Richards [7], eq. (1).

$$C = 640.EC_s \quad (1)$$

Where:

C - concentration of fertilizing salts, mg L⁻¹; and

ECs - electrical conductivity of the solution, dS m⁻¹.

Different concentrations were prepared based on eq. (1), corresponding to a salinity called "theoretical salinity". Thereafter, the actual electrical conductivity of the solutions was determined using a benchtop conductivity meter. A curve was adjusted correlating the concentration of the fertilizer solution with the electrical conductivity of these solutions, by means of a dispersion diagram. Subsequently, samples of 10 kg of the soil to be used in the main experiment were collected, which were air dried, sieved and placed in 8 L pots. The pots containing a 20 cm soil layer had perforated bases and a 2 cm layer of gravel was placed in the bottom and covered by a geotextile blanket (Bidim OP-30).

The soil was collected at the ESALQ campus, where it is called "Sertãozinho Series", at a depth of up to 0.50 m, considered the arable layer for this profile. The soil was classified as Yellow Red Latosol, sandy phase [8].

The soil moisture in the pots was increased from air dried to maximum retention capacity. This was done by applying the previously studied dilute solutions, with the objective of obtaining nine levels of electrical conductivity already corrected for the saturated soil extract paste (EC from 1.0 to 9.0 dS m⁻¹, with variation of 1.0 dS m⁻¹), with three replicates. For salinization, the values of the final concentration of fertilizers in the water (C_f) applied to the soil were those necessary to obtain the EC levels to be reached in the field stage of the experiment, already considering the dilution to the moisture of the saturated soil extract paste and the adsorption.

The proportion of nutrients from the solutions adopted for salinization was based on the Hoagland nutrient solution, described by Furlani [9] (Table 1).

Table 1. Nutrient concentration of the nutrient solution whose proportions were used for salinization.

Macronutrients (mg L ⁻¹)						Micronutrients (mg L ⁻¹)					
N	P	K	Ca	Mg	SO	B	Cu	Fe	Mn	Mo	Zn
200	31	293	100	24	32	0.2	0.03	3.4	1.1	0.05	0.2

Source: Hoagland, according to Furlani (1999).




Figure 1. Concentration of the fertilizer solution applied to obtain the desired EC in the saturation paste of the salinized soil used in the main experiment. Source: The Authors.

The result of the pre-test to ascertain the concentration of fertilizer solution applied to obtain the desired EC in the saturated soil extract paste is shown in Fig. 1.

2.3. Implementation of treatments

The experiment was conducted in a randomized block design, arranged in a 2 x 5 factorial scheme, with 6 replicates. The treatments were obtained by combining two forms of soil reclamation (R1 = continuous, and R2 = intermittent) and five salinity levels of the saturated soil extract paste (S1 = 2.0, S2 = 4.0, S3 = 6.0, S4 = 8.0, and S5 = 10.0 dS m⁻¹).

In the experimental area, 60 lysimeters were placed in 4 rows of 15 lysimeters, so that each of these containers represented an experimental plot. In each of the 6 blocks there were 10 experimental plots, corresponding to 2 systems and 5 salinity levels.

The drainage system of the tubular lysimeters was composed of holes located near the base of each lysimeter, where 19 mm diameter PVC pipes were inserted and sealed with epoxy and sealing material. The PVC pipes had length of 0.60 m and holes with 5 mm diameter around their

circumference spaced 0.05 m apart. In order to facilitate drainage and prevent soil transportation, a synthetic blanket (BIDIM OP - 20) was used as a filter on a 0.10 m layer of washed gravel.

In order to obtain the five proposed levels of salinity, the electrical conductivity of the saturated soil extract paste was raised to the following levels: S1 = 2.0, S2 = 4.0, S3 = 6.0, S4 = 8.0, and S5 = 10.0 dS m⁻¹) by the addition of nutritive saline solutions dissolved in water from the ESALQ supply system. The amount of salt used to prepare each solution was calculated based on the artificial salinization curve (Fig. 1) obtained in the previous experiment.

The composition of the solution used for salinization was the same as that indicated in the previous salinization curve, based on the proportions of Hoagland nutrient solution described by Furlani [9] (Table 1).

The saline solution was applied by a drip irrigation system at a flow rate of 8 L h⁻¹. The system was composed of pressure compensating button drippers. Each dripper was connected to a two-split divider in order to obtain uniform distribution of the solution at the soil surface. At the end of the applications, the electrical conductivity levels of the soil solution were measured by analyzing the solutions extracted from the soil 48 hours after salinization. The lysimeters were then covered with polyethylene plastic to avoid evaporation, thus enabling the soil inside to reach moisture close to field capacity.

Soil samples were collected from the lysimeters for physical and hydric analysis. The physical properties of the soil were analyzed based on the method described by Embrapa [10]. The soil textural fractions were determined by measuring the proportions of coarse sand, fine sand, silt, and clay by the pipette method, and were expressed as percentage. The soil particle density (Dp) was determined by the volumetric flask method, and the soil density (Ds) was determined by the test tube method, for deformed samples, both expressed in g cm⁻³ (Table 2).

Prior to salinization, soil samples were collected at depths of 0.00-0.20, 0.20-0.40 and 0.40-0.60 m for chemical characterization of soluble ions (Table 3). The solutions were prepared from a paste with saturation moisture and were extracted by means of suction, according to the method proposed by Richards [7].

Table 2. Physical-hydric characterization of the soil used in the experiment.

FC	PWP	AW	Ds	Dp	MP	TP	Texture			Textural Class
— cm ³ cm ⁻³ —			— g cm ⁻³ —				Sand	Silt	Clay	
							%			
0.23	0.09	0.15	1.30	2.64	27	50	73	8	19	Sandy loam

FC - moisture at soil field capacity; PWP – moisture at the permanent wilting point, determined at tensions of 6.0 and 1500 kPa, respectively; AW - soil available water; Ds - soil density; Dp – soil particle density; MP - soil macroporosity; TP - soil total porosity.

Source: The Authors.

Table 3.

Chemical characterization of the soluble ions of the soil before the salinization process, carried out in saturated soil extract paste.

Depth	pH	CE	Na ⁺	K ⁺
m		dS m ⁻¹	mg L ⁻¹	
0.00-0.20	8.27	1.04	82.50	46.40
0.20-0.40	7.87	1.29	106.60	35.70
0.40-0.60	7.97	1.02	61.20	24.00

Source: The Authors.

Table 4.

Chemical characterization of the soil used in the experiment before artificial salinization.

Ph	MO	P	S	K	Ca	Mg	Al	H+Al	SB	CEC	V	M
	g dm ⁻³	mg dm ⁻³				mmolc dm ⁻³					%	
6.3	11	174	16	3.4	5.1	27	<1	15	81.4	96.4	84	1

Source: The Authors.

Soil samples were also collected for chemical characterization before salinization. The concentrations of phosphorus (P) and potassium (K) were determined by the cation exchange resin method, expressed as mg dm⁻³. Exchangeable calcium (Ca²⁺), magnesium (Mg²⁺) and H + Al (to measure potential acidity) were extracted from the soil by a 1 mol L⁻¹ ammonium acetate solution and quantified by atomic absorption spectrophotometry [10] (expressed in cmol_c dm⁻³). From these contents we determined the cation exchange capacity (CEC at pH 7.00) and the sum of bases (SB), expressed in cmol_c dm⁻³. Base saturation (V) was expressed as percentage (Table 4).

2.4. Calculation and application of the washing water depths for leaching

The process of reclamation of the salinized soils consisted of the application of water at various depths for the leaching of fertilizer salts and reduction of the electrical conductivity. This was based on empirical considerations of the solute dynamics that recommends application of a water depth corresponding to twice the volume of pores, for fast calculation of the reclamation water depth for saline soils [11]. In a first step, an initial water depth was applied to raise the lysimeter soil to field capacity and only then were the reclamation washing depths applied. In both systems, continuous and intermittent, a volume of 176 L of water per lysimeter was applied, and in the intermittent system this volume was divided in two applications, with an interval of six days between applications. Soon after the applications, black polyethylene plastic sheets were placed over the lysimeters to prevent water evaporation. The water used came from the supply system of the ESALQ campus, which was the water source at the test site.

2.5. Measurement of soil salinity after washing

The changes in soil chemical characteristics in response to the application of the washing water at the various depths were evaluated by measuring the electrical conductivity and concentration of the remaining ions in the soil solution of each lysimeter. For this, the solution of the soil was obtained with the use of extractors and later the concentration was corrected to saturation moisture.

For this purpose, three ceramic capsule extractors were installed in the soil of each lysimeter, totaling 180 units. Each was composed of a PVC tube with a porous capsule at the lower end. The capsules were positioned at three depths in the soil profile (20, 40 and 60 cm).

To obtain the soil solution, tension of 80 kPa was applied in the chamber of each extractor, using a vacuum pump 48 hours after the end of the applying the water. The solutions were withdrawn from the extractors by a hospital syringe after 24 hours, time necessary for redistribution of the solution that was in equilibrium between the capsule and the soil. The samples were stored in acrylic tubes and then taken for analysis in a laboratory of the Department of Biosystems Engineering of ESALQ/USP.

In the laboratory the electrical conductivity of each solution extracted by the porous capsules and the concentration of the main ions were determined, which were corrected for the saturation moisture using eq. (2):

$$C_{CORRECTED} = \frac{C_{cp} \cdot U_{cp}}{M_s} \quad (2)$$

where:

$C_{CORRECTED}$ - electrical conductivity or concentration of ions in the saturated soil extract paste, estimated from the values determined in the soil solution, in dS m⁻¹ or mmol_c L⁻¹;

C_{cp} - electrical conductivity or ion concentration in the soil solution, obtained with the porous capsule extractor, in dS m⁻¹ or mmol_c L⁻¹;

M_{cp} - soil moisture during application of tension in the extractor capsule, in g g⁻¹; and M_s - soil saturation moisture (saturated paste), in g g⁻¹.

2.6. Evaluation of the performance of empirical equations

After the field experiment tests, five empirical equations found in the literature were used to estimate the EC of the soil solution after the application of the washing water as different depths: Volobuyev, according to Palácios [12]; Cordeiro [13]; Jury [14]; Hoffman [15]; and Reeve [16]. For the purposes of comparison, we used in the calculation the same leaching depths applied in the actual tests as well as the

same initial chemical conditions measured in the soils contained in the lysimeters.

Thus, EC values were calculated using the equations of Volobuyev, Cordeiro, Jury, Hoffman and Reeve, equations 3 to 7, respectively. It is important to note that some equations present the results in electrical conductivity while others present them in ion concentration. In this case, the results in EC were converted into concentration using a correlation between them obtained in the initial phase of the experiment.

$$EC_f = EC_i \cdot 10^{-\left(\frac{L}{\alpha}\right)} \quad (3)$$

where:

ECf - final electrical conductivity in the saturated soil extract, in dS m⁻¹;

ECi - initial electrical conductivity in the saturated soil extract, in dS m⁻¹;

L - water depth to be applied to the soil for salt leaching, in mm; and

α - coefficient, which depends on the content of chloride and soil texture.

$$EC_f = EC_i \cdot 10^{-\left(\frac{L}{2.025 \cdot (p)} \cdot \frac{70 - EC_r}{EC_i - EC_r}\right)} \quad (4)$$

where:

p - depth of soil to be reclaimed, in cm; and

ECr - electrical conductivity of washing water, in dS cm⁻¹.

$$C = 0.8 \cdot C_o \cdot \theta \cdot \left(\frac{D_s}{D_e}\right) \quad (5)$$

where:

C - concentration of salts in the soil solution after reclamation, in mg L⁻¹;

C_o - concentration of salts in the soil solution before reclamation, in mg L⁻¹;

θ - volumetric soil moisture, in cm³ cm⁻³;

D_s - depth of soil to be reclaimed, in cm; and

D_e - water depth to be applied in the soil for washing the salts, in cm.

$$C = C_o \cdot K \cdot \left(\frac{D_s}{D_e}\right) \quad (6)$$

where:

K - constant, varying with the type of soil and the method of water application.

$$EC_f = \frac{\left(\frac{La}{Ls} - 0.15\right) \cdot EC_i}{5} \quad (7)$$

where:

La - water depth to be leached, in cm; and

Ls - soil thickness to be reclaimed, in cm.

The performance of the equations was evaluated by comparing the final EC obtained with the use of these

equations and the experimental results measured in the lysimeters installed in the experimental area.

For this, we used the mean absolute error (MAE), root mean square error (RMSE); paired t-test at significance of 5%, Willmott concordance test [17], Nash-Sutcliffe efficiency index (ENS), Pearson linear correlation, and Camargo-Sentelhas performance index [18], which is the result of the product of the Pearson correlation coefficient (r) and the Willmott accuracy index (d). The values were obtained respectively by:

$$RMSE = \left[\frac{1}{N} \sum_{i=1}^N (O_i - P_i)^2 \right]^{0.5} \quad (8)$$

$$MAE = \frac{1}{N} \sum_{i=1}^N [O_i - P_i] \quad (9)$$

$$t = \sqrt{\frac{(n-1) \text{viés}^2}{(n-1)^2 - \text{viés}^2}} \quad (10)$$

$$d = 1 - \left[\frac{\sum_{i=1}^N (P_i - O_i)^2}{\sum_{i=1}^N ([P_i - O] + [O_i - O])^2} \right] \quad (11)$$

$$ENS = 1 - \frac{\sum_{i=1}^N (O_i - P_i)^2}{\sum_{i=1}^N (O_i - O)^2} \quad (12)$$

The data were also submitted to analysis of variance. When there was significance by the F-test, the means were compared by the Tukey test at probability of 5%. The data analyses were performed with R [19].

3. Results and discussion

3.1. Evaluation of the performance of empirical equations

According to the analysis of variance, there was a significant interaction (p < 0.01) between the factors reclamation system (continuous or intermittent) and salinity levels only for the washing volume pores in the experiment. An isolated effect of salinity was found for both the experiment and all the equations studied (Table 5).

There was no significant effect of the reclamation systems on the different equations. These results show that the reclamation systems have no effect on the studied equations, since most of them do not reach the refinement of indicating which system will be used to reclaim the soil, that is, whether intermittent or continuous.

Comparison of the systems at each salinity level revealed that for all levels of salinity the systems did not differ statistically. In general, for all the systems studied a gradual concentration effect on salinity levels was observed (Table 6).

This interaction of salinity influenced the results possibly due to the medium soil texture. The observed increase is consistent with that expected and proposed, for example, by Van der Sloot [20], who studied the influence of particle size in leaching tests.

Table 5.

Summary of analysis of variance (F-test) and statistical significance for the variables EC estimated and EC measured in reclamation systems.

SV	DF	Statistic (F)					
		Experiment	Volobuyev	Cordeiro	Jury	Hoffman	Reeve
System	1	185.94**	0.58 ^{ns}	2.66 ^{ns}	0.58 ^{ns}	0.58 ^{ns}	0.58 ^{ns}
Salinity	4	67.69**	2078.31**	701.91**	2078.77**	2077.25**	2078.01**
System x Salinity	4	12.82**	2.16 ^{ns}	1.65 ^{ns}	2.16 ^{ns}	2.16 ^{ns}	2.16 ^{ns}
CV (%)	-	18.317	3.897	1.879	3.896	3.898	3.897

**significant at 5% probability; ^{ns} non-significant; SV – source of variation; DF – degrees of freedom.

Source: The Authors.

Table 6.

Mean values of salinity in the experiment with the reclamation systems.

SYSTEMS	SALINITY LEVELS (dS m ⁻¹)				
	2.0	4.0	6.0	8.0	10.0
Intermittent	0.562C	0.646C	0.712BC	0.986BA	1.438A
Continuous	0.876C	1.181C	1.641B	1.836B	2.867A

Values followed by the same letter in the column do not differ according to the Tukey test at 5% probability.

Source: The Authors.

The author verified that larger soil specific surface areas per unit mass or volume may allow rapid dissolution at the surface.

3.2. Performance of the equations for soil salinity prediction in the intermittent system

The electrical conductivity values measured in the soil solution collected by the porous capsule extractors, and that simulated by the equations studied along the 1:1 line, as well as the regressions with the five washing equations in the intermittent reclamation system, are presented in Fig. 3.

High determination coefficient values (R^2_a) for the relations between the electrical conductivity values measured in the saturation extract (estimated from the electrical conductivity of the solution) and the values calculated by the different equations were observed (Fig. 2). These values were 0.9281 for Volobuyev, 0.9081 for Jury, 0.9481 for Hoffman and 0.9088 for Reeve. The exception was the value of 0.0817 for Cordeiro.

However, obtaining high determination coefficients alone is not sufficient to evaluate the fit between the measured and simulated data. In this sense, for some equations used there was no proximity to the 1:1 line and, even so, the values of R^2_a were very high. Legates and Davis [21] showed that the use of methods based on correlation indexes (such as the coefficient of determination) to quantify model performance can be inadequate.

When the Volobuyev reclamation equation was used, the estimated electric conductivity approached the measured values, and the trend line almost overlapped the 1:1 line (Fig. 2A). These results show that the Volobuyev equation is able to estimate the washing with good precision and presents reliability for the estimation of EC in the intermittent reclamation system. On the other hand, the values estimated by the Cordeiro, Jury, Hoffman and Reeve equations (Figs. 2B, 2C, 2D and 2E) performed poorly. The values found by the Hoffman equation underestimated the measured values of the electrical conductivity of the saturation extract, while the other three

equations overestimated the electrical conductivity values for the intermittent method.

In general, the equations tended to overestimate the measured values, mainly for the higher values. Among them, the equation of Cordeiro presented the greatest discrepancies. This performance is possibly due to the fact that this equation is very sensitive to the initial levels of soil salinity.

Table 7 presents the values of the Pearson linear correlation, Willmott concordance index, Camargo-Sentelhas performance index, mean absolute error, mean square error, and Nash-Sutcliffe efficiency coefficient, which were obtained in the comparisons between the EC values estimated and measured in the intermittent reclamation system.

When considering the linear correlation of Pearson, only the Cordeiro equation did not present acceptable significance, while the others were significant at 5%. This is due to the fact that the grouping of the estimated EC values in relation to the measured ones tends to improve the EC estimates. In relation to the Willmott coefficient, the equations presented high values, except for the Cordeiro equation, while the Volobuyev equation obtained a value of this index closest to the empirical value. The Volobuyev equation also showed a better result for the Camargo-Sentelhas performance index, as well as lower values of MAE and RMSE, making it the best equation for the intermittent reclamation system.

In relation to the E_{NS} values, the equations that had the best performance (values closer to 1) were the equations of Volobuyev (0.527) and Reeve (0.681). The other equations obtained negative values of this indicator, showing lower precision of their estimates. E_{NS} is an indicator widely used to evaluate models and equations. Its use in hydrology is due to the flexibility of application to several types of models and mathematical equations [22, 23]. In the literature, there is a greater indication of the E_{NS} parameter for the evaluation of model adjustments than the coefficient of determination, which is considered insensitive to the additive and proportional differences between model simulations.




Figure 2. Relationship between the electrical conductivity values of the saturated soil extract estimated with the equations and values measured from the electrical conductivity of the soil solution obtained with porous capsule extractors for intermittent reclamation (A - Volobuev; B - Cordeiro; C - Jury; D - Hoffman and E - Reeve)
Source: The Authors.

Table 7.

Pearson's correlation coefficient (r), Willmott's concordance index (d), Camargo-Sentelhas performance index (c), mean absolute error (MAE), root mean square error (RMSE), and efficiency coefficient of Nash-Sutcliffe (ENS) obtained in the comparisons between the EC values estimated and measured in the intermittent reclamation system

Equations	Test t	r	D	c	MAE	RMSE	ENS
Volobuev	1.280	0.832	0.900	0.857	0.182	0.201	0.527
Cordeiro	11.440	ns	0.282	0.621	0.975	1.078	-9.516
Jury	7.001	0.832	0.649	0.810	0.570	0.659	-2.936
Hoffman	10.989	0.878	0.716	0.819	0.327	0.364	-0.197
Reeve	6.008	0.832	0.719	0.828	0.455	1.493	0.681

Source: The Authors.




Figure 3. Relationship between the electrical conductivity values of the saturated soil extract estimated by the equations and the empirical electrical conductivity values of the soil solution obtained with porous capsule extractors for continuous reclamation (A - Volobuev; B - Cordeiro; C-Jury. D-Hoffman and E-Reeve).

Source: The Authors.

Table 8.

Pearson's correlation coefficient (r), Willmott concordance index (d), Camargo-Sentelhas performance index (c), mean absolute error (MAE), root mean square error (RMSE), and Nash-Sutcliffe efficiency coefficient (ENS) obtained in the comparisons between the estimated and measured EC values in the continuous reclamation system

Equations	Test t	r	D	c	MAE	RMSE	E _{NS}
Volobuev	10.566	0.898	0.870	0.799	0.897	1.007	-0.700
Cordeiro	0.755	ns	0.999	0.702	0.722	0.859	-0.239
Jury	5.170	0.897	0.989	0.908	0.374	0.475	0.621
Hoffman	1.137	0.898	0.735	0.675	1.143	1.264	-1.679
Reeve	6.978	0.898	0.977	0.987	0.774	0.581	0.434

Source: The Authors.

3.3. Performance of the equations for soil salinity prediction in the continuous system

The values of the coefficients of determination of the relations between the electric conductivity of the saturated soil extract and the values estimated by the different equations in the continuous system are presented in Fig. 3. The solutions were obtained with porous capsule extractors and the EC values were corrected as a function of moisture. The R^2_a estimated by the equations of Volobuyev, Cordeiro, Jury, Hoffman, and Reeve were respectively 0.9186, 0.0323, 0.9108, 0.9644, and 0.9463. In the continuous reclamation system, all the equations studied produced estimates that were lower than the measured values. The Cordeiro equation provided the best regression line in relation to the 1:1 line, but with very different values compared to the other equations. Since these dispersions are characterized by mathematical approximations that evaluate the accuracy, dispersion and distance of the simulated values in relation to the calculated ones, it can be affirmed that the prediction equations are not very efficient for the continuous system, that is, the values in the intermittent system are best described by empirical equations.

Analyzing specifically Fig. 3B, which represents the estimation by the Cordeiro equation, shows there is great dispersion of the points along the regression line. This behavior is different from that observed with the other equations, for which the estimated points are closer to the 1:1 line, showing good correlation between the measured and calculated values.

Considering the Pearson linear correlation, only the Cordeiro equation showed no significance at probability of 5% (Table 8). The equations of Cordeiro, Jury, and Reeve presented the best values for the Willmott coefficient. The Cordeiro equation provided the values closest to 1, which indicates perfect concordance. The MAE values were lower for the Jury equation (0.374), followed by Cordeiro (0.722), Reeve (0.774), and Volobuyev (0.897). The Hoffman equation presented the highest value (1.143). For the RMSE, the Jury equation provided the lowest value (0.475), followed by Reeve (0.581), while the Hoffman equation presented the highest value (1.264). Considering the ENS, the Reeve equation had the best performance (0.434), followed by Jury (0.621). For the other equations, this indicator showed negative values, indicating lower precision for estimation in the continuous reclamation system.

The results found in this study are different from the values obtained by Franco [24], who used the equations of Volobuyev, Cordeiro, Jury, Hoffman, and Reeve in a study with the same soil and two levels of salinity. The author suggested that the best equation was that of Cordeiro for calculation of the salt leaching depth in soils salinized with sodium chloride.

Franco [24] also pointed out that his results differ from some papers reviewed by him, which were highly variable due to the soil diversity and the conditions under which the studies were carried out. Thus, the results obtained by the reclamation equations may depend on soil physical-chemical factors, on the chemical composition of the washing water or on factors inherent to the method used. The lack of this

information prevents obtaining consistent results under varying experimental conditions.

The values of the Pearson linear correlation, Willmott concordance index, Camargo-Sentelhas performance index, mean absolute error, root mean square error, and Nash-Sutcliffe efficiency coefficient are reported in Table 8.

4. Conclusions

The reclamation leaching of salinized soils is possible for irrigation management and presents satisfactory results.

Among the leaching equations evaluated, that of Volobuyev represented the best the salinized soil remediation estimates in relation to the results obtained experimentally.

In general, the equations evaluated were more efficient in estimating for the intermittent reclamation system and the calculated values were underestimated when compared with experimental values.

References

- [1] Resende, R.S., Amorim, J.R.A., Cruz, M.A.S. and Meneses, T.N., Distribuição espacial e lixiviação natural de sais em solos do Perímetro Irrigado Califórnia. em Sergipe. Revista Brasileira de Engenharia Agrícola e Ambiental, 18 (Suplemento), pp. 46-52, 2014. DOI: 10.1590/1807-1929/agriambi.v18supps46-s52
- [2] Rhoades, J.D., Kandiah, A. and Mashali, A.M., The use saline water for crop production. FAO. Irrigation and Drainage, Paper 48, Rome, Italy, 1992.
- [3] Hoffman, G.J., Rhoades, J.D., Letey, J. and Sheng, F., Salinity management. In: Hoffman, G.J.; Howell, T.A.; Solomon, K.H., Eds. Management of farm irrigation systems. ASAE, Monograph, 9, cap.18, pp. 667-715, ASAE, St. Joseph, 1992.
- [4] FAO and ITPS. Status of the World's Soil Resources (SWSR) – Main report. Food and agriculture organization of the united nations and intergovernmental technical panel on soils. Rome, Italy. 2015, 650 P.
- [5] Dias, E.G.C.S., Avaliação de impacto ambiental de projetos de mineração no estado de São Paulo: a etapa de acompanhamento, PhD Dissertation, Escola Politécnica, Universidade de São Paulo, São Paulo, Brazil, 2001.
- [6] Rhoades, J.D. and Loveday, J., Salinity in irrigated agriculture. In: Stewart, D.R., Nielsen, D.R., Eds, Irrigation of agricultural crops. ASA. CSSA. SSSA. Madison, 1990. pp. 1089-1142.
- [7] Richards, L.A., Diagnosis and improvement of saline and alkali soils. United States Department of Agriculture, Washington, USA, 1954.
- [8] Embrapa. Centro Nacional de Pesquisa de Solos. Sistema Brasileiro de Classificação de Solos. 2. ed. Rio de Janeiro: Embrapa Solos, 2006.
- [9] Furlani, P.R., Silveira, C.P., Bolonhezi, D. and Faquin, V., Cultivo hidropônico de plantas. Boletim técnico IAC., 180, Campinas, Brazil, 1999.
- [10] Embrapa. Manual de análises químicas de solos, plantas e fertilizantes, 2 ed. revista e ampliada. Embrapa Informação Tecnológica, Brasília, Brazil, 2009.
- [11] Tavares Filho, A.N., Barros, M.F.C., Rolim, M.M. and Silva, E.F.F., Incorporação de gesso para correção da salinidade e sodicidade de solos salino-sódicos. Revista Brasileira de Engenharia Agrícola e Ambiental, 6(3), pp. 247-252, 2012. DOI:10.1590/S1415-43662012000300002
- [12] Palácios, O.V. y Aceves, E.N., Instructivo para el muestreo registro de datos e interpretacion de calidad del agua para riego agrícola. Colegio de postgraduados. Escuela Nacional de agricultura, Chapingo, Brasil, 1969.
- [13] Cordeiro, G.G., Salinidade em agricultura irrigada (conceitos básicos e práticos). Embrapa Semiárido, Petrolina, Brasil, 2001.
- [14] Jury, W.A., Jarrell, W.M. and Devitt, D., Reclamation of saline-sodic soils by leaching. Soil Science Society of America Journal, 43(6), pp. 1100-1106, 1979. DOI:10.2136/sssaj1979.03615995004300060008x
- [15] Hoffman, G.J., Alleviating salinity stress. Modifying the cRoot

- environment to reduce crop stress. American Society of Agricultural Engineers, chap.9, 1980, pp. 305-343.
- [16] Reeve, R.C., The relation of salinity to irrigation and drainage requirements. In: Proceedings of Third Congress on Irrigation and Drainage. International Commission on Irrigation and Drainage, 1957, pp.175-187.
- [17] Willmott, C.J. et al., Statistics for the evaluation and comparison of models. Journal of Geophysical Research, 90(C5), pp. 8995-9005, 1985. DOI: 10.1029/JC090iC05p08995
- [18] Camargo, A.P. and Sentelhas, P.C., Avaliação do desempenho de diferentes métodos de estimativa da evapotranspiração potencial do estado de São Paulo. Revista Brasileira de Agrometeorologia, 5(1), pp. 89-97, 1997.
- [19] R Development Core Team R: language and environment of statistical computing. Vienna. 2013.
- [20] Van Der Sloot, H.A., Heasman, L., Quevauviller, P.H., Harmonization of Leaching/Extraction Tests. Elsevier, Amsterdam, 1997.
- [21] Legates, D. and Davis, R., The continuing search for an anthropogenic climate change signal: limitations of correlation-based approaches. Geophysical Research Letters, 24 (18), pp. 2319-2322, 1997. DOI:10.1029/97GL02207
- [22] Gupta, H.V. and Kling, H., On typical range sensitivity and normalization of mean squared error and Nash-Sutcliffe efficiency type metrics. Water Resources Research, 47(W10601), 2011, DOI: 10.1029/2011WR010962
- [23] Mccuen, R.H., Knight, A. and Cutter, A.G., Evaluation of the Nash-Sutcliffe efficiency index. Journal of Hydrologic Engineering, 11(6), pp. 597-602, 2006. DOI: 10.1061/(ASCE)1084-0699(2006)11:6(597)
- [24] Franco, E.M., Eficiências de equações empíricas utilizadas para a determinar a lâmina de lixiviação de sais e modelagem da distribuição do sódio no solo, PhD Dissertation, Escola Superior de Agricultura Luiz de Queiroz, Universidade de São Paulo, Piracicaba, Brazil, 2013.

J.L.A. Silva, has a BSc. in Agricultural Engineering from Federal Rural Semi-Arid University (UFERSA), Brazil and a MSc. agricultural Systems Engineering from Luiz de Queiroz School of Agriculture, University of São Paulo (ESALQ/USP), Brazil. He is currently a PhD student in the graduate program in agricultural engineering of Federal University of Viçosa (UFV), Brazil. He has experience in agricultural engineering, with emphasis on water and soil engineering, mainly in the following subjects: water resources planning and management, soil and water conservation, salinization of irrigated areas and tolerance of crops to salinity.
ORCID: 0000-0002-4368-6079

S.N. Duarte, holds a BSc. in Agronomic Engineering from Federal Rural University of Rio de Janeiro (UFRRJ), Brazil, a MSc. in Irrigation and Drainage from the University of São Paulo (USP), Brazil, and a PhD in Agricultural Engineering from the Federal University of Viçosa (UFV), Brazil. He is currently an associate professor (level 2) at the University of São Paulo, Brazil. He has experience in the field of agricultural engineering, with emphasis on irrigation and drainage, working mainly in the following lines of research: hydrology, agricultural drainage, salinity and fertirrigation management.
ORCID: 0000-0002-1112-5701

D.D. Silva, holds a BSc. in Agronomy, MSc. and PhD in Agricultural Engineering from the Federal University of Viçosa, Brazil, and PhD. in Hydrologic Modeling from the Department of Agricultural and Biological Engineering of the University of Florida, USA. He is a full professor of in the Agricultural Engineering Department of Federal University of Viçosa (UFV), Brazil. He has experience in agricultural engineering, with emphasis on planning and management of water resources and conservation of soil and water, working mainly on the following topics: water resources management, ecohydrological modeling, surface runoff, water erosion and hydrological modeling.
ORCID: 0000-0001-9666-7421

N.O. Miranda, holds a BSc. in Agronomy from Federal University of Santa Maria (UFSM), Brazil, a MSc. in Agricultural Engineering from Federal University of Santa Maria, a PhD in Agronomy (phytotronics) from Federal

University of Ceará (UFC), Brazil, and a PhD. fellowship with the graduate program in Forestry Sciences of UFRN. He is currently professor at Federal Rural Semi-Arid University. He has experience in the area of agronomy, with emphasis on farm machinery and agricultural mechanization, working mainly on the following topics: soil preparation systems and soil management.

ORCID: 0000-0003-1808-572X



UNIVERSIDAD NACIONAL DE COLOMBIA

SEDE MEDELLÍN
FACULTAD DE MINAS

Área Curricular de Medio Ambiente

Oferta de Posgrados

Doctorado en Ingeniería - Recursos Hidráulicos
Maestría en Ingeniería - Recursos Hidráulicos
Maestría en Medio Ambiente y Desarrollo
Especialización en Aprovechamiento de
Recursos Hidráulicos
Especialización en Gestión Ambiental

Mayor información:

E-mail: acma_med@unal.edu.co
Teléfono: (57-4) 425 5105